

# Paint-Riter™ + Certified Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Issue date: 10/23/2020

Version: 1.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Trade name : Paint-Riter™ + Certified Black

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Marking.  
Restrictions on use : No additional information available

#### 1.3. Supplier

LA-CO Industries, Inc.  
1201 Pratt Boulevard  
Elk Grove Village, IL. 60007-5746  
Phone: (847) 956-7600  
Fax: (847) 956-9885  
E-mail: [customer\\_service@laco.com](mailto:customer_service@laco.com)



#### 1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887;  
全国应急中心 0532 8388 9090

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Flammable liquids, Category 2 H225 Highly flammable liquid and vapour.  
Serious eye damage/eye irritation, Category 2A H319 Causes serious eye irritation.  
Skin sensitisation, category 1B H317 May cause an allergic skin reaction.  
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336 May cause drowsiness or dizziness.  
Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labelling

Hazard pictograms (GHS) :

Signal word (GHS) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapour.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.

Precautionary statements (GHS) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical/ventilating/lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 - If on skin: Wash with plenty of water.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

# Paint-Riter™ + Certified Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

P312 - Call a poison center/doctor if you feel unwell  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P363 - Wash contaminated clothing before reuse.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS\_US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	% (w/w)	GHS classification
1-Methoxy-2-propanol	(CAS-No.) 107-98-2	35 - 55	Flam. Liq. 3, H226 STOT SE 3, H336
Ethanol	(CAS-No.) 64-17-5	10 - 30	Flam. Liq. 2, H225
Isopropanol	(CAS-No.) 67-63-0	1 - 7	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Rosin, fumarated, polymer with ethylene glycol and pentaerythritol	(CAS-No.) 68152-57-8	3 - 7	Eye Irrit. 2A, H319 Skin Sens. 1B, H317 Aquatic Chronic 4, H413
Carbon black	(CAS-No.) 1333-86-4	1 - 2	Carc. 2, H351

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
First-aid measures after skin contact : Wash skin thoroughly with mild soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water.  
First-aid measures after ingestion : Do NOT induce vomiting. Get medical advice/attention.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause drowsiness or dizziness.  
Symptoms/effects after skin contact : May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Causes serious eye irritation.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry chemical. Inert gas. Foam. Water spray. Water fog.  
Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour. Burning produces irritating, toxic and noxious fumes. Flammable vapours may accumulate in the container. Heavier than air, vapours may travel long distances along ground, ignite and flash back to source.

# Paint-Riter™ + Certified Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
- Reactivity : No dangerous reactions known.

### 5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses. Eliminate all ignition sources if safe to do so.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Avoid all eye and skin contact and do not breathe vapour and mist.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Stop leak if safe to do so. Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

- For containment : Eliminate all ignition sources. Stop the flow of material, if this is without risk.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Take up in non-combustible absorbent material and shove into container for disposal.

### 6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.
- Precautions for safe handling : No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid all eye and skin contact and do not breathe vapour and mist. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container tightly closed. Keep away from open flames, hot surfaces and sources of ignition.
- Incompatible products : Strong oxidizers.
- Incompatible materials : Heat sources.
- Heat and ignition sources : Keep away from heat, sparks and flame.
- Prohibitions on mixed storage : Keep away from incompatible materials.
- Storage area : Store in dry, cool, well-ventilated area.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Ethanol (64-17-5)		
ACGIH	Local name	Ethanol
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1884 mg/m <sup>3</sup>
ACGIH	ACGIH TWA (ppm)	1000 ppm
ACGIH	ACGIH STEL (ppm)	1000 ppm

# Paint-Riter™ + Certified Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

<b>Ethanol (64-17-5)</b>		
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL (TWA) (mg/m³)	1900 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
NIOSH	NIOSH REL (TWA) (mg/m³)	1900 mg/m³
NIOSH	NIOSH REL (TWA) [ppm]	1000 ppm
<b>Isopropanol (67-63-0)</b>		
ACGIH	Local name	2-Propanol
ACGIH	ACGIH TWA (mg/m³)	490 mg/m³
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (mg/m³)	960 mg/m³
ACGIH	ACGIH STEL (ppm)	400 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL (TWA) (mg/m³)	980 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	400 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
NIOSH	NIOSH REL (TWA) (mg/m³)	980 mg/m³
NIOSH	NIOSH REL (TWA) [ppm]	400 ppm
NIOSH	NIOSH REL (STEL) (mg/m³)	1225 mg/m³
NIOSH	NIOSH REL (STEL) [ppm]	500 ppm
<b>1-Methoxy-2-propanol (107-98-2)</b>		
ACGIH	Local name	1-Methoxy-2-propanol
ACGIH	ACGIH TWA (mg/m³)	369 mg/m³
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (mg/m³)	553 mg/m³
ACGIH	ACGIH STEL (ppm)	100 ppm
ACGIH	Remark (ACGIH)	Eye irr; CNS impair; A4 (Not classifiable as a Human Carcinogen: Agents which cause concern that they could be carcinogenic for humans but which cannot be assessed conclusively because of a lack of data. In vitro or animal studies do not provide indications of carcinogenicity which are sufficient to classify the agent into one of the other categories)
NIOSH	NIOSH REL (TWA) (mg/m³)	360 mg/m³
NIOSH	NIOSH REL (TWA) [ppm]	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m³)	540 mg/m³
NIOSH	NIOSH REL (STEL) [ppm]	150 ppm
<b>Carbon black (1333-86-4)</b>		
ACGIH	Local name	Carbon black
ACGIH	ACGIH TWA (mg/m³)	3 mg/m³ (I - Inhalable particulate matter)
ACGIH	Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)

# Paint-Riter™ + Certified Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Carbon black (1333-86-4)		
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
Rosin, fumarated, polymer with ethylene glycol and pentaerythritol (68152-57-8)		
Not applicable		

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust ventilation of closed transfer systems to minimize exposures. Avoid creating mist or spray. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

#### Hand protection:

In case of repeated or prolonged contact wear gloves. Butyl rubber gloves. short term. nitrile rubber gloves

#### Eye protection:

Chemical goggles or safety glasses

#### Respiratory protection:

None under normal use

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Solid marker containing liquid colored paint.
Colour	: Black
Odour	: Solvent
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 78.3 °C
Flash point	: 12.2 °C
Relative evaporation rate (butylacetate=1)	: < 1
Flammability (solid, gas)	: Flammable liquid and vapour.
Vapour pressure	: 11.8
Relative vapour density at 20 °C	: No data available
Relative density	: 1 – 1.33
Solubility	: insoluble in water.
Log Pow	: 0.7
Auto-ignition temperature	: 287 °C
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available

# Paint-Riter™ + Certified Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Oxidising properties : No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known.

### 10.2. Chemical stability

Flammable liquid and vapour.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

May release flammable gases. Burning produces irritating, toxic and noxious fumes. Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg
LD50 dermal rabbit	> 20000 mg/kg
LC50 Inhalation - Rat	133.8 mg/l/4h
ATE (oral)	10470 mg/kg bodyweight
ATE (vapours)	133.8 mg/l/4h
ATE (dust,mist)	133.8 mg/l/4h
Isopropanol (67-63-0)	
LD50 oral rat	5840 mg/kg
LD50 dermal rabbit	16.4 ml/kg
LC50 Inhalation - Rat [ppm]	> 10000 ppm/4h
ATE (oral)	5840 mg/kg bodyweight
ATE (dermal)	16400 mg/kg bodyweight
1-Methoxy-2-propanol (107-98-2)	
LD50 oral rat	4016 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat [ppm]	> 7000 ppm 6 hr
Carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg
LC50 Inhalation - Rat	> 4.6 mg/m <sup>3</sup> 4 h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified.

Ethanol (64-17-5)	
IARC group	1 - Carcinogenic to humans

# Paint-Riter™ + Certified Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

<b>Isopropanol (67-63-0)</b>	
IARC group	3 - Not classifiable

<b>Carbon black (1333-86-4)</b>	
IARC group	2B - Possibly carcinogenic to humans, Inhalation of dust

Reproductive toxicity : Not classified  
STOT-single exposure : May cause drowsiness or dizziness.

<b>Isopropanol (67-63-0)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

<b>1-Methoxy-2-propanol (107-98-2)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified  
Aspiration hazard : Not classified  
Viscosity, kinematic : No data available  
Likely routes of exposure : Inhalation. Skin and eye contact.  
Symptoms/effects after inhalation : May cause drowsiness or dizziness.  
Symptoms/effects after skin contact : May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Causes serious eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>Ethanol (64-17-5)</b>	
LC50 fish 1	14200 mg/l
EC50 crustacea	5012 mg/l

<b>Isopropanol (67-63-0)</b>	
LC50 fish 1	10000 mg/l

<b>1-Methoxy-2-propanol (107-98-2)</b>	
LC50 fish 1	20800 mg/l
EC50 crustacea	23300 mg/l
ErC50 (algae)	> 1000 mg/l

### 12.2. Persistence and degradability

<b>Paint-Riter™ + Certified Black</b>	
Persistence and degradability	Not established.

<b>Ethanol (64-17-5)</b>	
Biodegradation	> 96 % 28 d

<b>Isopropanol (67-63-0)</b>	
Persistence and degradability	Readily biodegradable.

<b>1-Methoxy-2-propanol (107-98-2)</b>	
Persistence and degradability	Readily biodegradable.
Biodegradation	96 % 28 d

<b>Carbon black (1333-86-4)</b>	
Persistence and degradability	Not readily biodegradable.

### 12.3. Bioaccumulative potential

<b>Paint-Riter™ + Certified Black</b>	
Log Pow	0.7
Bioaccumulative potential	Not established.

<b>Ethanol (64-17-5)</b>	
Bioaccumulative potential	Not expected to bioaccumulate.

# Paint-Riter™ + Certified Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Isopropanol (67-63-0)	
Bioaccumulative potential	Not expected to bioaccumulate.
1-Methoxy-2-propanol (107-98-2)	
Bioaccumulative potential	Not expected to bioaccumulate.

### 12.4. Mobility in soil

Paint-Riter™ + Certified Black	
Ecology - soil	Not established.

### 12.5. Other adverse effects

Other information : No additional information available.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.  
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Additional information : Handle empty containers with care because residual vapours are flammable.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint, 3, II  
UN-No.(DOT) : UN1263  
Proper Shipping Name (DOT) : Paint  
Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Packing group (DOT) : II - Medium Danger  
Hazard labels (DOT) : 3 - Flammable liquid



Other information :No supplementary information available

### Transportation of Dangerous Goods

Transport document description : UN 1263 PAINT, 3, II  
UN-No. (TDG) : UN 1263  
Proper Shipping Name (Transportation of Dangerous Goods) : PAINT  
Primary Hazard Classes : 3 - Class 3 - Flammable Liquids  
Packing group : II - Medium Danger

### Transport by sea

Transport document description (IMDG) : UN 1263 PAINT, 3, II  
UN-No. (IMDG) : 1263  
Proper Shipping Name (IMDG) : PAINT  
Class (IMDG) : 3 - Flammable liquids  
Packing group (IMDG) : II - substances presenting medium danger  
Limited quantities (IMDG) : 5 L

### Air transport

Transport document description (IATA) : UN 1263 PAINT, 3, II  
UN-No. (IATA) : 1263  
Proper Shipping Name (IATA) : PAINT



# Paint-Riter™ + Certified Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Class (IATA) : 3 - Flammable Liquids  
Packing group (IATA) : II - Medium Danger

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

##### Isopropanol (67-63-0)

Subject to reporting requirements of United States SARA Section 313

SARA Section 311/312 Hazard Classes	Fire hazard
-------------------------------------	-------------

#### 15.2. International regulations

##### CANADA

##### Ethanol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### Isopropanol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### 1-Methoxy-2-propanol (107-98-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### Carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### Rosin, fumarated, polymer with ethylene glycol and pentaerythritol (68152-57-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### EU-Regulations

No additional information available

##### 1-Methoxy-2-propanol (107-98-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

##### Carbon black (1333-86-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

##### Rosin, fumarated, polymer with ethylene glycol and pentaerythritol (68152-57-8)

Listed on ELINCS (European List of Notified Chemical Substances)

##### National regulations

##### Paint-Riter™ + Certified Black

All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

##### Ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)

##### 1-Methoxy-2-propanol (107-98-2)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on Taiwan National Chemical Inventory  
Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

##### Carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on Taiwan National Chemical Inventory  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Inventory of Existing Chemical Substances Produced or Imported in China (IECSC).

# Paint-Riter™ + Certified Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

### Carbon black (1333-86-4)

Listed on the Japanese ISHL (Industrial Safety and Health Law)

### Rosin, fumarated, polymer with ethylene glycol and pentaerythritol (68152-57-8)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on Taiwan National Chemical Inventory

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Not listed on Phillipines Inventory of Chemicals and Chemical Substances (PICCS)

Not listed on the AICS (Australian Inventory of Chemical Substances)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

### 15.3. US State regulations

#### Paint-Riter™ + Certified Black

State or local regulations

The Carbon black in this product is bound and is not respirable.  
California Prop. 65 warnings are not required.

Component	State or local regulations
Ethanol(64-17-5)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Isopropanol(67-63-0)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
1-Methoxy-2-propanol(107-98-2)	U.S. - Idaho - Occupational Exposure Limits - Ceilings; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs); U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Minnesota - Hazardous Substance List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York - Right to Know List of Hazardous Chemicals; U.S. - Washington - Permissible Exposure Limits - STELs; U.S. - Washington - Permissible Exposure Limits - TWAs
Carbon black(1333-86-4)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List

### SECTION 16: Other information

Data sources : ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Other information : None.

Full text of H-statements:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H413	May cause long lasting harmful effects to aquatic life.

Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.

# Paint-Riter™ + Certified Black

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	PBT: Persistent, Bioaccumulative, Toxic
	TWA: Time Weighted Average
	TSCA: Toxic Substances Control Act

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*