









SO WIDE. SO LIGHT. SO TRUE COLOR.

You've never seen welding this way before.

OUR BEST INNOVATIONS IN ONE HELMET.

optrel presents the most innovative and ergonomically optimal helmet to date, expanding the welder's field of vision without compromising on comfort. The unique nose cut-out floats above the nose to position the auto-darkening display closer to the eyes. This enlarges the field of vision 6 times compared to conventional welding masks, without adding extra weight.

The panorama view - in combination with the 2.5 shade at lightstate and the optrel True Color optics - opens an entirely new visual dimension to the welding experience.

The panoramaxx features optrel's patented Autopilot function. Our unique 5-sensor array measures the brightness of the welding arc and automatically adjusts to the correct shade level.

The panoramaxx also marks the launch of optrel's unique new power system. Featuring a lithium-polymer power pack in combination with high-performance solar cells and an external USB charging option, the panoramaxx is the energy-independent, maintenance-free choice for professional welders.

The panora maxx combines optrel's groundbreaking innovations with an unprecedented panorama view - making it the most advanced welding helmet of its time.

To match the optrel panoramaxx field of vision, a typical rectangular auto-darkening filter would need to be as large as this 180 x 120 mm panel!

MAXXIMIZE YOUR HORIZON. WITH OPTREL'S PANORAMAXX.





is still a lightweight at only 550 g.



WELCOME TO A NEW DIMENSION OF VIEWING. IN ALL PROCESSES.



AUTOPILOT

Detection of the arc brightness and fully automated shade level adjustment from 5 to 12.

Light Autopilot range for all important work sequences

inactive mode Adjusts automatically to the changing light conditions of the current welding method.

Automatic adjustment up to shade level 12!

* If preferred, the Autopilot can be deactivated for manual shade level selection.

5 6 7 8 9 10 11 12


Shade level





TRUE COLOR

A specially developed UV/IR filter allows the realistic color perception typical of optrel, bringing color to the welder's world.







You will see better: · during setup · during welding

- · during seam inspection
- · during grinding
- · during stitching Better vision improves your safety, comfort and efficiency

in the workplace.

Helmet system		Item no.	Main acces	Main accessories	
10	panoramaxx welding helmet black	1010.000		optrel parking buddy	5002.900
10	panoramaxx PAPR helmet black	4441.660		Front cover lens (5 pcs.)	5000.270
				Nose guard pad (2 pcs.)	5003.600
				Adjustable headband	5003.263
			J Comme	optrel bag for helmets	8000.100
an call to a care of the					
			Spare parts	and accessories	ltem no.
				er lens (5 pcs.) Micro USB connection (2 pcs.)	5000.270 5003.520
	G	6		rer lens (5 pcs.)	5000.010
				rd pad (2 pcs.)	5003.600
	208			veatband (2 pcs.)	5004.073
			6 Adjustabl	e headband (including	5003.263
			sweatban	d and comfortband)	
			7 0 6	1 (0)	500.00

7 Comfortband (2 pcs.)

9 Breast protector, leather

8a Head and neck protector, leather8b Head and neck protector PAPR, leather

5004.020 4028.016

4028.031

4028.015

THE HIGH-TECH WELDING MASK. SWISS MADE.

TECHNICAL DATA

out floats above the nose to position the auto-darkening filter closer to the welds er's eyes. True-Color filter protects at shade levels 2.5/5-12M with Autopilot (automatic shade selection), +/- 2 individual shade-preference adjustment, sensitivity control and opening delay we optional twilight function. Shade levels inactive: shade level 2,5 active, manual: shade level 7-12 Autopilot Automatic protection level regulation					
Autopilot Automatic protection level regulation across a range from 5-12 with individual calibration option of ± 2 Power supply Solar cells, lithium-polymer battery, rechargeable by USB-cable Battery life 300 to 500 charging cycles Sensors Five Sensors Sensitivity Infinitely adjustable, now with "super high" sensitivity Switching time bright to dark: 0.090 ms at room temperature 0.070 ms at 55°C dark to bright: 0.1 s to 2.0 s (with twilight function) Field of vision Depending on headband setting,	Description	extra-large field of vision: the nose cut- out floats above the nose to position the auto-darkening filter closer to the weld- er's eyes. True-Color filter protects at shade levels 2.5/5-12M with Autopilot (automatic shade selection), +/- 2 in- dividual shade-preference adjustment, sensitivity control and opening delay with			
Automatic protection level regulation across a range from 5-12 with individual calibration option of ± 2 Power supply Solar cells, lithium-polymer battery, rechargeable by USB-cable Battery life 300 to 500 charging cycles Sensors Five Sensors Sensitivity Infinitely adjustable, now with "super high" sensitivity Switching time bright to dark: 0.090 ms at room temperature 0.070 ms at 55°C dark to bright: 0.1 s to 2.0 s (with twilight function) Field of vision Depending on headband setting,	Shade levels	inactive:	shade level 2,5		
across a range from 5-12 with individual calibration option of ± 2 Power supply Solar cells, lithium-polymer battery, rechargeable by USB-cable Battery life 300 to 500 charging cycles Sensors Five Sensors Sensitivity Infinitely adjustable, now with "super high" sensitivity Switching time bright to dark: 0.090 ms at room temperature 0.070 ms at 55°C dark to bright: 0.1 s to 2.0 s (with twilight function) Field of vision Depending on headband setting,		active, manual:	shade level 7-12		
rechargeable by USB-cable Battery life 300 to 500 charging cycles Sensors Five Sensors Sensitivity Infinitely adjustable, now with "super high" sensitivity Switching time bright to dark: 0.090 ms at room temperature 0.070 ms at 55°C dark to bright: 0.1 s to 2.0 s (with twilight function) Field of vision Depending on headband setting,	Autopilot	across a range from 5-12 with individual			
Sensors Five Sensors Sensitivity Infinitely adjustable, now with "super high" sensitivity Switching time bright to dark: 0.090 ms at room temperature 0.070 ms at 55°C dark to bright: 0.1 s to 2.0 s (with twilight function) Field of vision Depending on headband setting,	Power supply				
Sensitivity Infinitely adjustable, now with "super high" sensitivity Switching time bright to dark: 0.090 ms at room temperature 0.070 ms at 55°C dark to bright: 0.1 s to 2.0 s (with twilight function) Field of vision Depending on headband setting,	Battery life	300 to 500 charging c	cycles		
"super high" sensitivity Switching time bright to dark: 0.090 ms at room temperature 0.070 ms at 55°C dark to bright: 0.1 s to 2.0 s (with twilight function) Field of vision Depending on headband setting,	Sensors	Five Sensors			
0.090 ms at room temperature 0.070 ms at 55°C dark to bright: 0.1 s to 2.0 s (with twilight function) Field of vision Depending on headband setting,	Sensitivity				
Field of vision Depending on headband setting,	Switching time	0.090 ms at room tem 0.070 ms at 55°C dark to bright:			
100 x 50 mm standard industry ADF	Field of vision	2.3x to 6.3x field of vis	sion of a		

Optical class:			
Scattered light:			
Homogeneity:	1		
Angular dependence:	2		
Welding mask: up to 220 °C / 428 °I	F		
Front cover lens: up to 137 $^{\circ}$ C / 279 $^{\circ}$ F			
Ultraviolet / Infrared Protection: maximum protection at any shade level			
-10°C to + 70°C / 14°F to 158°F			
-20°C to + 80°C / -4°F to 176°F			
550 g / 19,4 oz			
Any electric arc welding process Electrode Welding (Stick Welding, SMAW) / MIG / MAG (GMAW) / GMAW High melting rate process / Flux Cored Wire Welding / TIG welding (GTAW) / Plasma Arc Welding / Plasmacutting & Oxy-gas Welding / Grinding in Grind Mode			
Prohibited for laser welding!			
Welding helmet, manual, storage bag, Micro USB cable, warranty card and one front cover lens			
CE, ANSI Z87.1 (ADF and helmet shell), EAC, complies with CSA Z94.3			
2 years			
1 year warranty extension (except batteries) for online product registration with the first 6 months. http://register.optrel.com			
	Scattered light: Homogeneity: Angular dependence: Welding mask: up to 220 °C / 428 °I Front cover lens: up to 137 °C / 279 °F Ultraviolet / Infrared Protection: maximum protection at any shade leve -10°C to + 70°C / 14°F to 158°F -20°C to + 80°C / -4°F to 176°F 550 g / 19,4 oz Any electric arc welding process Electrode Welding (Stick Welding, SMA / MIG / MAG (GMAW) / GMAW High melting rate process / Flux Cored Wire Welding / TIG welding (GTAW) / Plasm Arc Welding / Plasmacutting & Oxy-ga Welding / Grinding in Grind Mode Prohibited for laser welding! Welding helmet, manual, storage bag, Micro USB cable, warranty card and one front cover lens CE, ANSI Z87.1 (ADF and helmet shell), EAC, complies with CSA Z94.3 2 years 1 year warranty extension (except batteries) for online product registration with the first 6 months.		

Your optrel Reseller:



optrel AG industriestrasse 2 CH-9630 wattwil switzerland www.optrel.com info@optrel.com

