

SXE 425 TurboTec (600131000) Random Orbit Sander

(220-240 V / 50 Hz); Cardboard box

- Vario (V)-electronics for working at customised speeds to suit various application materials.
- Thumbwheel for Speed Preselection
- TurboBoost: allows additional power reserves to be employed for achieving maximum removal
- Power Control System: No scratches when placing the running machine on the material
- Removable side handle
- Dust-proof ball bearing for long service life of the machine
- Sturdy aluminium die cast bearing housing
- Grip area with non-slip softgrip surface
- Dust cassette with filter for working without connecting a vacuum cleaner
- Extraction possibility by means of connecting an all-purpose vacuum cleaner

Link to Product

Illustration



Product may differ from Image

Characteristics		
Diameter of backing pad	125 mm / 5 "	
No-Load Speed	4200 - 11000 /min	
Rated input power	320 W	
Output power	160 W	
Revolutions at rated load	9000 /min	
Swing diameter	5 mm / 3/16 "	
Weight (without power cable)	2.3 kg / 5.1 lbs	
Cable length	2.5 m / 8 ft	
Vibration		

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 11/15

Surface grinding	3.5 m/s²	
Uncertainty of measurement K	1.5 m/s²	
Polishing	4.5 m/s²	
Uncertainty of measurement K	1.5 m/s²	
Noise emission		
Noise emission Sound pressure level	82 dB(A)	
	82 dB(A) 93 dB(A)	

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 11/15