

W 9-125 Quick (600374000) Angle Grinders

(220-240 V / 50 - 60 Hz); Cardboard box

- Low fatigue as never before: compact angle grinder with smallest handle circumference in its class for perfect ergonomics
- New, patent-pending Metabo Marathon motor with up to 50% more torque and up to 20% higher overload capacity for quicker material removal and longer service life
- Now even faster: Metabo Quick System for tool-free disc change at the touch of a button by means of quick flange nut
- Tool-free adjustable guard; twist-proof mounting
- Metabo S-automatic safety clutch: direct mechanical decoupling in case of jamming of the disc minimises kickback for high safety and swift progress; proven for decades
- Gear housing can be mounted turned in 90° steps for left-handed operation or for cutting
- Auto-stop carbon brushes to protect the motor

Link to Product

Illustration



Product may differ from Image

System Application Images



Characteristics	
Grinding wheel Ø	125 mm / 5 "
Rated input power	900 W
Output power	550 W
No-Load Speed	10500 /min /min
Revolutions at rated load	7500 /min

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 10/15

Metabo | Metabo-Allee 1 | 72622 Nürtingen | Phone 07022 72-0 | Fax 07022 72-25 95 | metabo@metabo.de | www.metabo.com

Torque	2.5 Nm / 22 in-lbs
Spindle thread	M 14
Weight (without power cable)	2.1 kg / 4.6 lbs
Cable length	4 m / 13 ft
Vibration	
Surface grinding	6 m/s²
Uncertainty of measurement K	1.5 m/s²
Grinding with sandpaper	2.5 m/s ²
Uncertainty of measurement K	1.5 m/s²
Noise emission	
Sound pressure level	93 dB(A)
Sound power level	104 dB(A)
Uncertainty of measurement K	3 dB(A)

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 10/15