

## GEP 950 G Plus (600627000) Die Grinder

(220-240 V / 50 - 60 Hz); Cardboard box

- High torque and compact design thanks to robust planetary gear
- Spindle lock for simple change of tools
- Paddle switch with dead man function: Safe to operate due to an ergonomically integrated non-slip switch
- Aluminium die-cast bearing flange for long service life of the machine
- Vario-Constamatic (VC) Electronics for working with customised speeds for the materials used that remain almost constant under load
- Thumbwheel for preselection of speed
- Electronic safety shutdown of the motor if the tool jams for safe working
- Restart protection: prevents unintentional startup after power cut
- Electronic overload protection for long service life
- Precise collar for stationary use
- Removable protective rubber cap for comfortable and safe working
- Slim housing for ideal handling
- Precision collet for precise concentricity
- Metabo Marathon motor with patented dust protection for long service life
- The specialist: handy grinder with especially high torque; ideal for grinding inner and outer surfaces in combination with flap wheels (see Accessories)

### [Link to Product](#)

#### Illustration



Product may differ from Image

#### System Application Images



#### Characteristics

No-Load Speed

2500 - 8700 /min

Rated input power	950 W
Output power	510 W
Revolutions at rated load	7200 /min
Collar diameter	43 mm / 1 11/16 "
Collet bore of the collet chuck	6 mm / 0.2362 "
Weight (without power cable)	1.7 kg / 3.7 lbs
Cable length	4 m / 13 ft

#### Vibration

Surface grinding	2.3 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

#### Noise emission

Sound pressure level	87 dB(A)
Sound power level	98 dB(A)
Uncertainty of measurement K	3 dB(A)