

KHE 3251 (600659190) Combination Hammer

(220-240 V / 50 - 60 Hz); Plastic carry case

- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Ergonomic housing shape for chiselling tasks without side handle.
- Hammer stop for drilling in rotary only mode
- Rotation stop for chiselling
- Clockwise and Anti-clockwise Rotation
- Metabo Quick: Quick change between SDS Plus hammer chuck and quick-action keyless chuck for drilling in wood and metal
- Vario (V)-electronics for working at customised speeds to suit various application materials.
- Metabo Marathon motor with patented dust protection for long service life
- High performance hammer action, precisely mounted in a housing made of aluminium alloy: long-lasting and robust
- Metabo S-automatic torque limiting clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly.
- Cable-protecting ball spout for best freedom of motion when working

[Link to Product](#)

Illustration



Product may differ from Image

System Application Images



Characteristics

Max single blow energy (EPTA)	3.1 J
Maximum impact rate	4470 /min

Rated input power	800 W
Drill-Ø concrete with hammer drills	32 mm / 1 1/4 "
Drill-Ø masonry with core bits	82 mm / 3 1/4 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	35 mm / 1 3/8 "
No-Load Speed	0 - 1150 /min
Revolutions at rated load	920 /min
Torque	20 Nm / 177 in-lbs
Bit retainer	SDS-plus
Impact power	222 J/s
Collar diameter	50 mm / 1 31/32 "
Weight (without power cable)	3.6 kg / 7.9 lbs
Cable length	4 m / 13 ft

Vibration

Hammer drilling concrete	12.9 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Chiseling	10.9 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	91 dB(A)
Sound power level	102 dB(A)
Uncertainty of measurement K	3 dB(A)