

## KGS 254 M (602540190) Crosscut and Mitre Saw; With Sliding Function

(220-240 V / 50 - 60 Hz); Cardboard box

- Compact light weight, suitable also for one-handed transport
- Sliding function for wide work pieces.
- Easy transport thanks to ergonomically-designed handles and saw head lock
- Robust die-cast aluminium design for the highest demands
- Effective dust extraction via integrated dust scoop
- Fast and precise setting of common angles using stop points
- Laser for exact display of the cutting line (mains powered, no batteries required)
- Infinitely extendable table width extension, removable to put long panels, slabs etc. underneath
- Bright LED work light for illumination of the cutting line (mains powered, no batteries required)
- High sliding rear fence profiles for safe sawing
- Material clamp for secure fixing of the work piece from the top or front
- Depth stop for easy creation of grooves
- Saw head can be inclined to the left, with additional angle range for undercuts
- All scales and operating elements are visible from the working position and can be operated intuitively
- Easy saw blade change by means of spindle lock: No dismantling of the pendulum protective cover required

### [Link to Product](#)

#### Illustration



Product may differ from Image

#### System Application Images



#### Characteristics

Dimensions	790 x 515 x 515 mm / 2.6 x 1.7 x 1.7 ft
Maximum cutting width 90°/45°	305 / 205 mm // 12 / 8 1/16 "

Maximum cutting depth at 90°/45°	92 / 47 mm // 3 5/8 / 1 13/16 "
- Straight cut 90°/90°	305 x 92 mm / 12 x 3 5/8 "
- Double mitre 45°/45°	205 x 47 mm / 8 1/16 x 1 27/32 "
Turntable setting left/right	47 / 47 °
Saw blade tilt left/right	47 / 2 °
Saw blade	254 x 30 mm / 10 x 1.181 "
Rated input power S1 100%	1450 W
Rated input power S6 20%	1800 W
No-Load Speed	4500 /min /min
Revolutions at rated load	3150 /min
Max. cutting speed	60 m/s / 197 ft/s
Weight	16.3 kg / 36 lbs
Cable length	2 m / 7 ft