



The Ideal Flange Fit-Up Tool!



8 - 12" (200–300 mm) Internal Fit-Up Clamp



4 - 8" (100–200 mm) Internal Fit-Up Clamp



2 - 4" (50–100 mm) Internal Fit-Up Clamp

NOTE: The Internal Fit-up Clamp is an alignment tool. A separate lifting device to support the flange weight is recommended.

Part No.	Description	Weight	
		Lb.	Kg.
784103 784102 784100	8 - 12" (200–300 mm) Internal Fit-up Clamp 4 - 8" (100–200 mm) Internal Fit-up Clamp 2 - 4" (50–100 mm) Internal Fit-up Clamp	28.0 8.5 2.5	12.7 3.9 1.1

Sumner Manufacturing Co, Inc. www.sumner.com


DISTRIBUTED BY:

Sumner - U.S. 7514 Alabonson Road • Houston, TX 77088 • Ph: 281-999-6900 • Fax: 281-999-6966 Sumner - Canada 75 Saltsman Drive, Unit 5 • Cambridge, Ontario N3H 4R7 • Ph: 519-653-5300 • Fax: 519-653-5305 Sumner - Netherlands Midden Engweg 21 • NL-3882TS Putten • The Netherlands • Ph: +31 (0) 85 489 0284 • europeansales@sumner.com

Sumner - U.K. Unit 3 Kempton Road • Keytec 7 Business Park • Pershore, Worcestershire WR10 2TA • Ph: (44) 01386 556278 • Fax: (44) 01386 556776

Internal Fit-Up Features:

- Can be used on all standard weld neck flanges and great with slip-on flanges
- Contact points stainless steel
 a standard feature
- One piece construction no loose pieces
- Quick action operation
- Priced right



Two independently operated internal mandrels align flange to pipe even if internal dimensions differ.

Simple Operation



1. Tighten jaws to clamp pipe I.D.



 Mount flange on second set of pipe jaws, adjust for gap and tighten jaws for final fit-up.