



ADJUSTABLE WRENCHES

90

90 SERIES


ergo®



9072



9072P



- Adjustable wrenches developed according to the scientific ERGO™ process
- Standards: ISO 6787, DIN 3117, ASME B107.8M - 1996 and BS 6333
- High performance alloy steel
- Comfortable non slip thermoplastic grip handle
- Scale in mm for pre adjusting and accurate measurement
- The jaw does not fall out even at maximum opening of the wrench
- Head angle 15° provides better accessibility
- Left going screw
- P series: Reversible jaw for pipe use
- Black finish. Precision hardened and anti-corrosion treated

| | 731415 | | A mm | B mm | C mm | D mm | g |
|--------|------------|---|---------|---------|---------|---------|-------|
| 9070 | 0100170 | 5 | 158 | 20 | 4.9 | 11.3 | 139 |
| 9070 P | 0103416 | 5 | 158 | 21 | 4.9 | 11.3 | 139 |
| 9071 | 0100194 | 5 | 208 | 27 | 6.0 | 12.9 | 272 |
| 9071 P | 0103430 | 5 | 208 | 28 | 6.0 | 12.9 | 272 |
| 9072 | 0055609 | 5 | 257 | 31 | 8.7 | 15.2 | 425 |
| 9072 P | 0056354 | 5 | 257 | 33 | 8.7 | 15.2 | 430 |
| 9073 | 0101702 | 5 | 308 | 34 | 11.9 | 17.6 | 730 |
| 9073 P | 0101726 | 5 | 308 | 35 | 11.9 | 17.6 | 745 |

90C

90 SERIES


ergo®



9072 C



9072 PC



- Adjustable wrenches developed according to the scientific ERGO™ process
- Standards: ISO 6787, DIN 3117, ASME B107.8M - 1996 and BS 6333
- High performance alloy steel
- Comfortable non slip thermoplastic grip handle
- Scale in mm for pre adjusting and accurate measurement
- The jaw does not fall out even at maximum opening of the wrench
- Head angle 15° provides better accessibility
- Left going screw
- P series: Reversible jaw for pipe use
- Chrome plated, precision hardened and anti-corrosion treated

| | 731415 | | A mm | B mm | C mm | D mm | g |
|---------|------------|---|---------|---------|---------|---------|-------|
| 9070C | 0100187 | 5 | 158 | 20 | 4.9 | 11.3 | 139 |
| 9070 PC | 0103423 | 5 | 158 | 21 | 4.9 | 11.3 | 139 |
| 9071C | 0100200 | 5 | 208 | 27 | 6.0 | 12.9 | 272 |
| 9071 PC | 0103447 | 5 | 208 | 28 | 6.0 | 12.9 | 272 |
| 9072 C | 0055616 | 5 | 257 | 31 | 8.7 | 15.2 | 425 |
| 9072 PC | 0056361 | 5 | 257 | 33 | 8.7 | 15.2 | 430 |
| 9073 C | 0101719 | 3 | 308 | 34 | 11.9 | 17.6 | 730 |
| 9073 PC | 0101733 | 3 | 308 | 35 | 11.9 | 17.6 | 745 |