

C-Series – Cast Iron Series

Stationary – 415 Volt

Built in Australia.

This industrial range of air compressors use air receivers to the Australian Standard AS1210 as required by the Department of Occupational Health and Safety.

- ◆ Rated to AS4637.
- ◆ Heavy duty cast iron pumps.
- ◆ V-Twin or W-Triple cylinder configuration.
- ◆ Fully balanced flywheel with large cooling blades.
- ◆ Low speed, single stage pump.
- ◆ Auto stop/start pressure switch.
- ◆ TECO totally enclosed fan cooled motor.
- ◆ Supported by TECO National Service Network.
- ◆ Forklift feet.
- ◆ Warranty.
 - 2 years on pump.
 - 5 years on tank.
 - 1 year on motor.



C 50



C 120

Dimensions (mm)	Length	Width	Height	Weight (kg)
C 40	1,450	450	850	143
C 50	1,500	520	1,000	185
C 75	1,500	540	1,450	215
C 120	1,500	590	1,160	326

Product Code	Displacement CFM	L/min	Free Air Delivery CFM	L/min	Motor Hp	Tank Litres	Max. Pressure	Pump Model	Cylinders
C 40	19.6	555	13.3	376	4.0	125	130psi	LB 40	W-Triple
C 50	23.6	668	16.3	461	5.5	155	130psi	LB 50	V-Twin
C 75	33.0	934	21.5	609	7.5	155	130psi	LB 75	W-Triple
C 120	52.0	1,471	36.4	1,030	10.0	300	130psi	UB 100B	W-Triple

* Heavy Duty Anti Vibration Pads available for stationary units.



CFM x 28.3 = Litres per minute
 Displacement & FAD calculated at 100psi.
 Specifications/configuration may change at any time without notice.

For improved air quality please consider our Refrigerated Dryers and Filters.