

CAPACITOR DISCHARGE (CD) STUD WELDER

MODEL : CD-3500



- Contact-type CD Stud Welder
- Stud Range: M2 to M8 (Heavy Duty Cycle)
- Materials include Mild Steel, Stainless Steel, Aluminium, Brass, including galvanized and copper finishes.
- Suitable for thin sheets
- Suitable for HVAC applications
- Easy to operate.
- Powerful, Compact & Robust

COMES WITH ACCESSORIES: -



STUD WELDING GUN



EARTH LEAD



SPANNER



CHUCK

TECHNICAL DATA: -

Welding Current Output Mode	Electrolytic Capacitor
Capacitor Model (Uf)	144000
Stud Welding Range (Stud Diameter mm / material)	2-10 / low carbon steel 2-8 / stainless steel 2-8 / aluminium alloy 2-8 / zinc
Input Fuse (A)	10
Charging Voltage (V)	35-200
Power (W)	800
Welding time (S)	0.001-0.003
Welding Speed (pcs/min)	15-40
Power Voltage (V)	AC220 -2P (110/380/415 can customized)
Frequency (HZ)	50/60
Protection Grade	IP31
Welding Stud Length (mm)	Standard 5-35
Welding Range (mm)	2-10
Torch Cable (m)	3 (can customized)
Weight (KG)	22
Dimensions (mm)	600* 220 * 300