

# ZERO-SPAT™ ASPR Anti-Spatter

## Technical Data Sheet

### Description:

Chemtools® Zero Spat™ ASPR Wet Formula Anti Spatter forms a wet film that prevents weld spatter from sticking to weld equipment, fixtures and metal surfaces during welding. The spatter and residue can easily be wiped away after the welding is completed, leaving a light corrosion protective film on the metal.

### Product Features:

- ◆ Fast drying, solvent based.
- ◆ Silicone free.
- ◆ Prevents rust and corrosion.
- ◆ Non-flammable.

### Benefits:

- ◆ Spatter wipes away.
- ◆ Improves productivity.
- ◆ Economical in use.
- ◆ Eliminates the need for chiselling and grinding, after welding
- ◆ Easy clean-up.
- ◆ Does not cause weld porosity.

### Application:

Shake aerosol can vigorously for 10 seconds.

Spray an even light coating onto the work piece and or welding nozzle at a distance of 150 to 200mm using a sweeping motion. Allow to solvent to evaporate before welding. Product should be used with adequate ventilation.

### Storage:

Store in a cool, at a room temperature between 5°C to 30°C. Do not place in direct sunlight or near any heat source. Do not leave in vehicle cabins.

### Safety:

Avoid breathing any fumes, mists and vapours. Use of approved breathing apparatus is required for more than minimal exposure. Always work in areas with adequate ventilation to allow solvent fumes to dissipate. If the material gets into the eyes, flush thoroughly with clear water for fifteen minutes; then seek medical treatment. Avoid skin contact. Observe all safety precautions. It is important when using solvent based materials or solvents to keep away from open flames or ignition source.



Unit 2/14-16  
Lee Holm Road  
St Marys NSW 2760

Ph: 1300 738 250  
Fax: 02 9623 3670

[info@chemtools.com.au](mailto:info@chemtools.com.au)  
[www.chemtools.com.au](http://www.chemtools.com.au)

# ZERO-SPAT™ ASPR Anti-Spatter

**PRECAUTIONS:** This product capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the material.

**Warranty:** All products purchased from or supplied by Chemtools are subject to terms and conditions set out in the contract. Chemtools warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Chemtools is considered accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Chemtools makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.

**Date of issue: November 2012**

## Technical Data Sheet



Unit 2/14-16  
Lee Holm Road  
St Marys NSW 2760

**Ph:** 1300 738 250  
**Fax:** 02 9623 3670

[info@chemtools.com.au](mailto:info@chemtools.com.au)  
[www.chemtools.com.au](http://www.chemtools.com.au)