



A NEW FORCE IN CHEMICAL MANUFACTURING

Unit 2, 14-16 Lee Holm Road
St Marys NSW 2760
Australia

Ph: 1300 738 250 (Australia)
Ph: +61 2 9833 9766 (International)
Fax: 02 9623 3670

sales@chemtools.com.au
www.chemtools.com.au

TECHNICAL DATA SHEET

OCTOBER 2014

PRODUCT NAME

CT-DSPR Zero Spat™ Anti-Spatter

PRODUCT RANGE

Part Number	Available Size
CT-DSPR-300	300g Aerosol



Refer to MSDS for product safety guidelines

CT-DSPR Zero Spat™ Anti-Spatter

Chemtools® Zero Spat™ DSPR Dry Formula Anti Spatter forms a dry white film that prevents weld spatter from sticking to weld equipment, fixtures and metal surfaces during welding. The spatter and residue can easily be wiped or brushed away after the welding is completed.

PRODUCT FEATURES

- | | | |
|----------------|-----------------|-------------------|
| - Fast Drying | - Silicone-Free | - No Oil Residues |
| - Long Lasting | - Good Adhesion | - Non-Flammable |

BENEFITS:

- Usable on any MIG/MAG welding, manual, automatic and robotic applications
- Improves productivity
- Eliminates the need for chiselling and grinding, after welding
- Easy clean up

APPLICATION:

Shake aerosol can vigorously for 20 - 30 seconds after the internal ball starts to rattle. Spray an even coating onto the work piece and/or welding nozzle at a distance of 150 to 200 mm using short strokes. Allow to air dry before welding. Product should be used with adequate ventilation.

STORAGE:

Store at room temperature between 5°C to 30°C. Do not place in direct sunlight or near any heat source. Do not leave in vehicle cabins.

SAFETY:

Avoid breathing any fumes, mists and vapours. Use of approved breathing apparatus is required for more than minimal exposure. Always work in areas with adequate ventilation to allow solvent fumes to dissipate. If the material gets into the eyes, flush thoroughly with clear water for fifteen minutes, then seek medical treatment. Avoid skin contact. Observe all safety precautions. It is important when using solvent based materials or solvents to keep away from open flames or ignition source.

PRECAUTIONS:

This product is capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the material.

WARRANTY:

All products purchased from or supplied by Chemtools® are subject to terms and conditions set out in the contract. Chemtools® warrants only that its products meet the specifications designated as such herein, or in other publications. All other information supplied by Chemtools® is considered accurate, but is furnished upon the express condition. The customer shall make its own assessment to determine the products suitability for a particular purpose. Chemtools® makes no other warranty, either expressed or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or products will not infringe any patent.