



## K17T AIR COMPRESSOR – 415V THREE PHASE

PISTON DISPLACEMENT (to AS4637)	428 L/MIN ~ 15.1 CFM
FREE AIR DELIVERY (to AS4637)	292.6 L/MIN ~ 10.3 CFM
MAXIMUM CUT OUT PRESSURE	1000 KPA ~ 145 PSI
COMPRESSOR PUMP	TWIN CYLINDER, SINGLE STAGE, ITALIAN MADE
MOTOR	2.25 KW ~ 3.0 HP 415 V THREE PHASE 50HZ <b>NOTE: NOT SUPPLIED WITH LEAD &amp; PLUG</b>
REQUIRED CIRCUIT BREAKER	10AMP **
RECEIVER	58 LITRE (STATIC), TO AS1210, AUSTRALIAN MADE
DIMENSIONS	970mm L X 440mm W X 780mm H
WEIGHT	80 KG*
AIR OUTLET	1/4" BSP

\* APPROX ONLY

\*\* INDICATIVE ONLY, PLEASE CHECK WITH YOUR ELECTRICIAN



### FEATURES

- AUSTRALIAN DESIGNED AND BUILT
- INDUSTRIAL GRADE HAMMERTONE ENAMEL FINISH
- CAST IRON CYLINDER PUMP
- ELECTRIC MOTOR OVERLOAD
- WARRANTY: 3 YEARS ON PUMP, 1 YEAR ON ALL OTHER COMPONENTS

[www.pilotair.com.au](http://www.pilotair.com.au)  
[sales@pilotair.com.au](mailto:sales@pilotair.com.au)