

K30-V AIR COMPRESSOR – 415V THREE PHASE

PISTON DISPLACEMENT (to AS4637)	871.8 L/MIN ~ 30.8 CFM
FREE AIR DELIVERY (to AS4637)	681 L/MIN ~ 24.1 CFM
MAXIMUM CUT OUT PRESSURE	1100 KPA ~ 160 PSI
COMPRESSOR PUMP	TWIN CYLINDER, TWO STAGE, ITALIAN MADE
MOTOR	5.5 KW ~ 7.5 HP 415V THREE PHASE 50HZ NOTE: NOT SUPPLIED WITH LEAD & PLUG
REQUIRED CIRCUIT BREAKER	25 AMP **
RECEIVER	176 LITRE (STATIC, VERTICAL), TO AS1210, AUSTRALIAN MADE
DIMENSIONS	700mm L X 900mm W X 2040mm H
WEIGHT	190 KG*
AIR OUTLET	3/4" BSP

* APPROX ONLY

** INDICATIVE ONLY, PLEASE CHECK WITH YOUR ELECTRICIAN



FEATURES

- AUSTRALIAN DESIGNED AND BUILT
- COMPACT FOOTPRINT
- INDUSTRIAL GRADE HAMMERTONE ENAMEL FINISH
- CAST IRON CYLINDER PUMP
- ELECTRIC MOTOR OVERLOAD
- WARRANTY: 3 YEARS ON PUMP, 1 YEAR ON ALL OTHER COMPONENTS