



K30SI AIR COMPRESSOR – 415V THREE PHASE

PISTON DISPLACEMENT (to AS4637)	871 L/MIN ~ 30.8 CFM
FREE AIR DELIVERY (to AS4637)	681 L/MIN ~ 24.1 CFM
MAXIMUM CUT OUT PRESSURE	1100 KPA ~ 160 PSI
COMPRESSOR PUMP	TWIN CYLINDER, TWO STAGE, ITALIAN MADE
MOTOR	5.5 KW ~ 7.5 HP 415 V THREE PHASE 50HZ NOTE: NOT SUPPLIED WITH PLUG
NOISE LEVEL	66 d(B)a
REQUIRED CIRCUIT BREAKER	25 AMP **
RECEIVER	NOT SUPPLIED. A SEPARATE 147 LITRE RECEIVER IS RECOMMENDED
DIMENSIONS	900mm L X 640mm W X 1100mm H
WEIGHT	220 KG*
AIR OUTLET	3/4" BSP

* APPROX ONLY

** INDICATIVE ONLY, PLEASE CHECK WITH YOUR ELECTRICIAN



FEATURES

- ITALIAN DESIGNED AND BUILT
- OVER TEMPERATURE PROTECTION
- THERMOSTATICALLY CONTROLLED COOLING FANS
- CAST IRON CYLINDER PUMP
- ELECTRIC MOTOR OVERLOAD
- WARRANTY: 1 YEAR ON ALL COMPONENTS