

## **K50-V AIR COMPRESSOR- 415V THREE PHASE**

PISTON DISPLACEMENT (to AS4637)
FREE AIR DELIVERY (to AS4637)
MAXIMUM CUT OUT PRESSURE
COMPRESSOR PUMP

**MOTOR** 

REQUIRED CIRCUIT BREAKER

RECEIVER DIMENSIONS WEIGHT

AIR OUTLET

1120 L/MIN ~ 39.6 CFM 888 L/MIN ~ 31.3 CFM 1100 KPA ~ 160 PSI

TWIN CYLINDER, TWO STAGE, ITALIAN MADE 7.5 KW ~ 10 HP 415V THREE PHASE 50HZ

NOTE: NOT SUPPLIED WITH LEAD & PLUG

32 AMP \*\*

220 LITRE (STATIC, VERTICAL), TO AS1210, AUSTRALIAN MADE

730mm L X 1030mm W X 2040mm H

270 KG\* 3/4" BSP

\* APPROX ONLY
\*\* INDICATIVE ONLY, PLEASE CHECK WITH YOUR ELECTRICIAN



## **FEATURES**

- AUSTRALIAN DESIGNED AND BUILT
- COMPACT FOOTPRINT
- INDUSTRIAL GRADE HAMMERTONE ENAMEL FINISH
- CAST IRON CYLINDER PUMP
- ELECTRIC MOTOR OVERLOAD
- WARRANTY: 3 YEARS ON PUMP, 1 YEAR ON ALL OTHER COMPONENTS

www.pilotair.com.au sales@pilotair.com.au