



K50 AIR COMPRESSOR – 415V THREE PHASE

PISTON DISPLACEMENT (to AS4637)	1120 L/MIN ~ 39.6 CFM
FREE AIR DELIVERY (to AS4637)	888 L/MIN ~ 31.3 CFM
MAXIMUM CUT OUT PRESSURE	1100 KPA ~ 160 PSI
COMPRESSOR PUMP	TWIN CYLINDER, TWO STAGE, ITALIAN MADE
MOTOR	7.5 KW ~ 10.0 HP 415 V THREE PHASE 50HZ NOTE: NOT SUPPLIED WITH LEAD & PLUG
REQUIRED CIRCUIT BREAKER	32 AMP **
RECEIVER	216 LITRE (STATIC), TO AS1210, AUSTRALIAN MADE
DIMENSIONS	1450mm L X 640mm W X 1300mm H
WEIGHT	220 KG*
AIR OUTLET	3/4" BSP

* APPROX ONLY
** INDICATIVE ONLY, PLEASE CHECK WITH YOUR ELECTRICIAN



FEATURES

- AUSTRALIAN DESIGNED AND BUILT
- INDUSTRIAL GRADE HAMMERTONE ENAMEL FINISH
- CAST IRON CYLINDER PUMP
- ELECTRIC MOTOR OVERLOAD
- WARRANTY: 3 YEARS ON PUMP, 1 YEAR ON ALL OTHER COMPONENTS

www.pilotair.com.au
sales@pilotair.com.au