



## K50SI AIR COMPRESSOR – 415V THREE PHASE

PISTON DISPLACEMENT (to AS4637)	1119 L/MIN ~ 39.6 CFM
FREE AIR DELIVERY (to AS4637)	888 L/MIN ~ 31.3 CFM
MAXIMUM CUT OUT PRESSURE	1100 KPA ~ 160 PSI
COMPRESSOR PUMP	TWIN CYLINDER, TWO STAGE, ITALIAN MADE
MOTOR	7.5 KW ~ 10 HP 415 V THREE PHASE 50HZ <b>NOTE: NOT SUPPLIED WITH PLUG</b>
NOISE LEVEL	68 d(B)a
REQUIRED CIRCUIT BREAKER	32 AMP **
RECEIVER	NOT SUPPLIED. A SEPARATE 216 LITRE RECEIVER IS RECOMMENDED
DIMENSIONS	900mm L X 640mm W X 1100mm H
WEIGHT	220 KG*
AIR OUTLET	3/4" BSP

\* APPROX ONLY  
\*\* INDICATIVE ONLY, PLEASE CHECK WITH YOUR ELECTRICIAN



### FEATURES

- ITALIAN DESIGNED AND BUILT
- OVER TEMPERATURE PROTECTION
- THERMOSTATICALLY CONTROLLED COOLING FANS
- CAST IRON CYLINDER PUMP
- ELECTRIC MOTOR OVERLOAD
- WARRANTY: 1 YEAR ON ALL COMPONENTS