

KUM425 / KUM500SWF



The Unimig 425 SWF is a powerful high duty cycle machine designed for medium to heavy fabrication and rural applications. Combining smooth arc characteristics with complete reliability, the Unimig 425 SWF is the unit to satisfy all the demands of the professional welder. Features a completely enclosed KT 50 wire feed unit which helps prevent dust and moisture fouling your wire and contaminating your weld. Fitted standard with a geared four roller drive system ensuring consistent wire feed and smooth welding. It comes with fully covered 10 Metre interconnecting cables and wheels for increased maneuverability.

The Unimig 500 SWF is a powerful high duty cycle machine designed for heavy fabrication and rural applications. Combining smooth arc characteristics with complete reliability. The Unimig 500 SWF is the unit to satisfy all the demands of the professional welder. The completely enclosed KT 90 wire feed unit helps prevent dust and moisture fouling your wire and contaminating your weld. Fitted standard with a geared four roller drive wire feed system ensuring consistent wire feed and smooth welding. It comes with, fully covered 10 Metre interconnecting cables and wheels for increased maneuverability.



UNIMIG 425 SWF

UNIMIG 500 SWF

UNI-MIG KT 90

CE

TECHNICAL SPECIFICATION **UNIMIG 425 SWF UNIMIG 500 SWF** PART NUMBER KUM425SWF KUM500SWF PRIMARY INPUT VOLTAGE 415V 3 Phase 415V 3 Phase WELDING CURRENT 40-400 Amps 50-450 Amps VOLTAGE STEPS 30 50 DUTY CYCLE 40°C 50% @ 400 Amps 35% @ 450 Amps 60% @ 360 Amps 60% @ 410 Amps 100% @ 320 Amps 100% @ 280 Amps WELDING VOLTAGE RANGE DC 16 - 34V 16 - 36V WIRE SIZE (mm) 0.6 - 1.6mm Ferrous 0.6 - 1.6mm Ferrous 0.9 - 1.6mm Aluminium 0.9 - 1.6mm Aluminium 0.6 - 1.6mm Stainless Steel 0.6 - 1.6mm Stainless Steel 0.9 - 2.4mm Flux cored 0.9 - 2.4mm Flux cored DIMENSIONS (mm) 1270 x 940 x 600mm 1270 x 940 x 600mm WEIGHT (Kgs) 182 Kgs 199 Kgs TORCH OPTIONS: SB38 4 Metre / 5 Metre SB38 4 Metre / 5 Metre ARB 400 / 12ft / 15ft & 17ft ARB 400 / 12ft / 15ft & 17ft TWC 4 / 12ft / 15ft & 17ft TWC 4 / 12ft / 15ft & 17ft

425SWF / 500SWF Package Includes: Argon regulator, Gas Hose, 10 Metre Earth lead SB38 3 Metre MIG torch, •(Optional 4 Metre)

Amp-Volt Meter Amp-Volt Meter