


TRS 315 EDV

TRS 315 EDVS (SLOW SPEED)

315MM SWIVEL HEAD COLDSAW



FEATURES

- Italian made quality
- Swivel head 45° left & right
- Trigger switch operation
- Quick locking double vice for burr free cutting
- Recirculating coolant system with electric pump
 - Creates instant flow of coolant
 - Flood applied coolant creates a cooler cut for increased finish quality & blade life
- Adjustable material stop for repetitive production
- Safety emergency stop switch
- Comes complete with blade
- Optional stand available
Part# MC-STAND315
- Slow speed (20rpm) model also available, designed specifically for cutting stainless-steel



Part No.	MC-TRS315EDV-1	MC-TRS315EDV-3	MC-TRS315EDVS-3	
Motor	2hp Single Phase (240V)	3hp Three Phase (415V)	3hp Three Phase (415V)	
Blade Speed	Single Speed 40rpm	2 Speed 40 / 80rpm	2 Speed Slow 20 / 40rpm	
Blade Size	315mm			
Blade Bore	32mm			
Weight	165kg			
Cutting Capacity				
Cutting Angle				
90°	55mm	90mm	80mm	115 x 70mm
45° (L&R)	50mm	80mm	70mm	70 x 70mm

OPTIONAL ACCESSORIES & CONSUMABLES



ROLLER CONVEYORS

- Straight & V-Shape Single Roller Conveyors
- 3m length, 300mm - 600mm width Conveyors



SYNTHETIC METAL WORKING FLUID

Cutting fluid designed for use with MACC coldsaws, bandsaws & metal working machinery that use a recirculating coolant system with fluid storage tank.

Part No.	Description
MF-5LITRE	5 Litre MACC Synthetic Metal Working Fluid
MF-20LITRE	20 Litre MACC Synthetic Metal Working Fluid



HIGH-SPEED STEEL DM05 (M2) COLD SAW BLADES

Suitable for cutting all metals including mild steel, stainless-steel, aluminium copper, brass and more

Part No.	Diameter	Thickness	Bore	# Teeth
C3152532-140	315mm	2.5mm	32mm	140
C3152532-160	315mm	2.5mm	32mm	160
C3152532-180	315mm	2.5mm	32mm	180
C3152532-200	315mm	2.5mm	32mm	200
C3152532-220	315mm	2.5mm	32mm	220