



Inverter Series

**PORTABLE
WELDING SOLUTIONS**



Trusted by the best

welding.com.au
1300 300 884



The WIA Inverter Series

**YOU'VE ASKED FOR IT & WE'VE DELIVERED.
WIA'S RANGE OF INVERTER WELDING MACHINES ARE
PORTABLE & EASY TO TRANSPORT FROM JOB TO JOB.**

Cost effective, power efficient and portable, WIA's inverters contribute to a more productive workplace.

Selection Chart

MIG & MULTI-PROCESS

MACHINE	RATED OUTPUT	PHASE	MACHINE WEIGHT	TYPICAL APPLICATIONS
Weldmatic 200i	200 A at 24.5 V, 15% Duty Cycle	1	13kg	Rural Applications, Construction Sites, Automotive Panel Repair, Exhaust Repair.
Weldmatic 250i	250 A at 26.5 V, 20% Duty Cycle	1	25.5kg	
Weldmatic 350i	350 A at 31.5 V, 60% Duty Cycle	3	93kg	Medium to Heavy Fabrication and General Industrial Fabrication.
Weldmatic 500i	500 A at 39 V, 60% Duty Cycle	3	96kg	

ARC & TIG

MACHINE	RATED OUTPUT	PHASE	MACHINE WEIGHT	TYPICAL APPLICATIONS
Weldarc 145i	145 A at 25.8 V, 15% Duty Cycle	1	4.1kg	Onsite Maintenance.
Weldarc 185i	185 A at 27.4 V, 20% Duty Cycle	1	5.5kg	
Weldarc 200i AC/DC	200 A at 18 V, 15% Duty Cycle	1	19.5kg	

Reliability & Performance Second to None!

ALL OF OUR INVERTER PRODUCTS ARE SUPPORTED BY AN AUSTRALIA WIDE SERVICE NETWORK, SO YOU CAN BE GUARANTEED YOU'RE BUYING RELIABILITY & PERFORMANCE.

2 YEAR
UNLIMITED WARRANTY

*Power Source Only

The Weldmatic 200i & 250i and the Weldarc 200i AC/DC are backed with a 2 year unlimited warranty*, covering parts and labour.

*Power Source Only

3 YEAR
GOLD SHIELD WARRANTY

The Weldmatic 350i & 500i, Weldarc 145i & 185i are backed with WIA's industry leading 3 year warranty, covering parts and labour.



MIG & Multi-Process

**RELIABLE & HIGH PERFORMING WELDING SOLUTIONS
SUITABLE FOR MIG, STICK & LIFT ARC TIG WELDING.**

- For operator safety, all of our MIG and multi-process welders feature a built in thermal protection device that will cut in if the machine is operated beyond its safe thermal operating zone.
- All WIA MIG and multi-process machines suit gas shielded and flux-cored wires.
- Built in VRD delivers added safety when operating in Stick or Lift-TIG mode and meets the requirements of site work. Fully compliant to Australian Standards AS60974.1 and AS1674.2 CAT C.



Weldmatic 200i

Part No: CP137-0

✓ GASLESS**✓ ALUMINIUM MIG****✓ MILD STEEL****200 AMP SINGLE PHASE WELDER**

With 200 A of MIG, 170 A of Stick and 200 A of TIG capability the Weldmatic 200i is suitable for rural applications, construction sites, automotive panel repair and exhaust repair.

EASY SET-UP & ADJUSTMENT

The control panel allows easy selection for gas and wire type, with infinitely variable voltage and wire speed, indicated on the digital display. A suggested setting chart allows the Weldmatic 200i to be setup quickly and easily.

PACKAGE INCLUDES

- Euro Gun Cable (3m)
- Work Lead (3m)
- Industrial Twist Lock Electrode Holder (3m)
- Gas Regulator
- Drive Rollers 0.6/0.8mm V Groove; 0.9/1.2mm Knurled (Gasless)
- Tips (0.6/0.8/0.9/1.2mm)
- ES6 Steel Sample Wire (0.8mm)

PORTABLE

At only 13kg, the Weldmatic 200i is lightweight and portable, making it suitable for onsite maintenance.

QUICK & EASY GUN CABLE ASSEMBLY

Supplied with a tradesman quality gun and cable complete with euro connector for easy fitting and removal.

SPOOL CAPACITY

Suits 1kg & 5kg spool.

OPTIONAL ACCESSORIES PART NO.

Gas Bottle Trolley	AM356
Weldmatic Workshop Trolley	AM357

ALUMINIUM MIG ACCESSORIES PART NO.

Drive Roller	W26-3/8
Nylon Liner (0.9/1.2mm)	BE43115X
Austmig Wire 5356 1.0mm 2kg	M5356102KG



PRIMARY VOLTAGE	RATED PRIMARY CURRENT	MAX. PRIMARY CURRENT	REC. GEN. kVA*	SUPPLY PLUG	RATED OUTPUT @ 40C (10 MIN)	WELDING CURRENT RANGE	WIRE SIZE RANGE (MM)	SHIPPING INFO	MACHINE WEIGHT	IP RATING
240 Vac - 50/60 Hz	14 Amps	36 Amps	10 kVA	15 Amps	200 A at 24.5 V, 15% Duty Cycle 77 A at 17.9 V, 100% Duty Cycle	30 - 200 Amps	0.6 - 0.9 solid 0.8 - 1.2 cored 1.0 aluminium	20kg H: 470 W: 320 L: 675	13kg	IP21S

*Due to variation between generators by different manufacturers, it is impossible for WIA to validate operation from all generators. Therefore, WIA recommends that operation of equipment on the generator is confirmed before purchasing either welder of the generator.



Weldmatic 250i

Part No: CP138-1

✓ GASLESS**✓ ALUMINIUM MIG****✓ MILD STEEL****250 AMP SINGLE PHASE WELDER**

With 250 A of MIG, 200 A of Stick and 250 A of Lift-TIG capability the Weldmatic 250i is suitable for rural applications, construction sites, automotive panel repair and exhaust repair.

EASY SET-UP & ADJUSTMENT

The control panel allows easy selection for gas and wire type, with infinitely variable voltage and wire speed, indicated on the digital display.

PACKAGE INCLUDES

- > Euro Gun Cable (3.6m)
- > Work Lead (3m)
- > Industrial Twist Lock Electrode Holder (3m)
- > Gas Regulator
- > Drive Rollers – 0.9/1.2mm V Groove, 0.9/1.2mm Knurled (Gasless)
- > Tips (0.6/0.8/0.9/1.2mm)

SPOOL CAPACITY

Suits 5kg & 15kg spool.

OPTIONAL ACCESSORIES**PART NO.**

Trolley with Drawer AM358

QUICK & EASY GUN CABLE ASSEMBLY

Supplied with a tradesman quality gun and cable complete with euro connector for easy fitting and removal.

PORTABLE

At 25.5kg, the Weldmatic 250i is portable and comes supplied with two handles for easy two person lift, making it suitable for onsite maintenance.

**ALUMINIUM MIG ACCESSORIES****PART NO.**

Drive Roller (x2)	WF029
Nylon Liner (0.9/1.2mm)	BE43115X
Austmig Wire 5356 1.0mm 6kg	M535610S
Austmig Wire 5356 1.2mm 6kg	M535612S

PRIMARY VOLTAGE	RATED PRIMARY CURRENT	MAX. PRIMARY CURRENT	REC. GEN. kVA*	SUPPLY PLUG**	RATED OUTPUT @ 40C (10 MIN)	WELDING CURRENT RANGE	WIRE SIZE RANGE (MM)	SHIPPING INFO	MACHINE WEIGHT	IP RATING
240 Vac - 50/60 Hz	20.2 Amps	45 Amps	13 kVA	15 A fitted. 20 A required.	250 A at 26.5 V, 20% Duty Cycle 112 A at 19.6 V, 100% Duty Cycle	30 - 250 Amps	0.6 - 0.9 solid 0.8 - 1.2 cored 1.0 aluminium	36kg L: 735mm W: 355mm H: 565mm	25.5kg	IP21S

*Due to variation between generators by different manufacturers, it is impossible for WIA to validate operation from all generators. Therefore, WIA recommends that operation of equipment on the generator is confirmed before purchasing either welder or the generator.

**For full rated output, a 20 A plug and supply is required with a 25 A circuit breaker. 15 Amp plug is for commissioning purposes only.





MIG & MULTI-PROCESS

Weldmatic 350i

✓ ALUMINIUM MIG

✓ STEEL

✓ ARC AIR GOUGING

✓ CORED WIRE



**FITTED WITH 32A
3 PHASE PLUG**

350 AMPS
OF GENUINE RATED POWER

**VOLTAGE SENSING
WIREFEEDER COMPATIBILITY**

EQUIPMENT & OPTIONS

PART NO.

Weldmatic 350i	CP139-3
W66 Wirefeeder	WFL016
W65 Wirefeeder	WFL015
Trolley with Drawer	AM358

ALUMINIUM MIG ACCESSORIES

PART NO.

Drive Roller (x2)	WF029
Nylon Liner (0.9/1.2mm)	BE43115X
Austmig Wire 5356 1.0mm 6kg	M535610S
Austmig Wire 5356 1.2mm 6kg	M535612S

Part No: CP139-1 - [Package with W66 Wirefeeder and Trolley with Drawer]

PACKAGE INCLUDES

- W66 4 Roll Drive Wirefeeder
- Euro Gun Cable (3.6m) With Bernard Centerfire 0.9mm Tip
- Industrial Twist Lock Electrode Holder (3m)
- Interconnecting Lead (10m)
- Gas Regulator
- Work Lead (10m)
- Drive Rollers – 0.9/1.2mm V Groove & 0.9/1.2mm Knurled

**350 AMP
3 PHASE WELDER**

Ideal for medium to heavy fabrication, and all general industrial fabrication applications.

DIGITAL METERS

Digital Volt and Amp meters retain last weld information and allow precise set-up.

**FLEXIBILITY
& POWER**

Optimal weld characteristics provide high quality results on steel, stainless steel and aluminium, plus the power to comfortably run all popular sizes of solid and flux-cored wires. With the capacity to run 1.6mm flux-cored wire, the 350i can handle a wide range of applications.

**VARIABLE
ARC CONTROL**

The package features allow full control of the arc. Infinite Voltage control and Arc control to adjust arc harshness, and Arc Start to control the wire starting speed.

SPOOL CAPACITY

Suits 5kg & 15kg spool.

FAN ON DEMAND™

The Fan-on-Demand™ cooling system uses less power and generates less noise by only operating when needed, meaning improved efficiency, less maintenance and a safer working environment.



PRIMARY VOLTAGE	RATED PRIMARY CURRENT	MAX. PRIMARY CURRENT	REC. GEN. kVA*	RATED OUTPUT @ 40C (10 MIN)	WELDING CURRENT RANGE	SIZE OF WIRE/ ELECTRODE RANGE (MM)	SHIPPING INFO	IP RATING
380/415 Vac - 50/60Hz 3 Phase	19.4 Amps	25 Amps	15 kVA	Stick (MMA) - 350 A at 34 V, 60% Duty Cycle, 271 A at 30.8 V, 100% Duty Cycle	25 - 350 Amps	Carbon Arc Max. 6mm	Machine Weight: 93kg	IP21S
				TIG - 350 A at 24 V, 60% Duty Cycle 271 A at 20.8 V, 100% Duty Cycle			Shipping Weight: 131kg	
				MIG - 350 A at 31.5 V, 60% Duty Cycle 271 A at 27.6 V, 100% Duty Cycle		0.9-1.6 solid 0.9-1.6 cored	L: 1100mm W: 570mm H: 1080mm	

*Due to variation between generators by different manufacturers, it is impossible for WIA to validate operation from all generators. Therefore, WIA recommends that operation of equipment on the generator is confirmed before purchasing either welder or the generator.



MIG & MULTI-PROCESS

Weldmatic 500i

✓ **ALUMINIUM MIG**

✓ **STEEL**

✓ **ARC AIR GOUGING**

✓ **CORED WIRE**



**FITTED WITH 32A
3 PHASE PLUG**

500 AMPS
OF GENUINE RATED POWER

**VOLTAGE SENSING
WIREFEEDER COMPATIBILITY**

EQUIPMENT & OPTIONS

PART NO.

Weldmatic 500i	CP140-3
W65 Wirefeeder	WFL015
W66 Wirefeeder	WFL016
Trolley with Drawer	AM358

ALUMINIUM MIG ACCESSORIES

PART NO.

Drive Roller (x2)	WF072
Nylon Liner (0.9/1.2mm)	BE43115X
Nylon Liner (1.2/1.6mm)	BE44215N
Austmig Wire 5356 1.0mm 6kg	M535610S
Austmig Wire 5356 1.2mm 6kg	M535612S

Part No: CP140-1 - [Package with W65 Wirefeeder and Trolley with Drawer]

PACKAGE INCLUDES

- W65 4 Roll Drive Heavy Duty Wirefeeder
- Euro Gun Cable (3.6m) with Bernard Centerfire 0.9mm Tip
- Industrial Twist Lock Electrode Holder (3m)
- Drive Rollers – 0.9/1.2 & 1.2/1.6mm V Groove, 0.9/1.2 & 1.2/1.6mm Knurled
- Interconnecting Lead (10m)
- Work Lead (10m) with Heavy Duty G Clamp
- Gas Regulator

500 AMP 3 PHASE WELDER

Ideal for medium to heavy fabrication, and all general industrial fabrication applications.

FLEXIBILITY & POWER

Optimal weld characteristics provide high quality results on steel, stainless steel and aluminium, plus the power to comfortably run all popular sizes of solid and flux-cored wires. With the capacity to run 1.6mm flux-cored wire, the 500i can handle a wide range of applications.

VARIABLE ARC CONTROL

The package features allow full control of the arc. Infinite Voltage control and Arc control to adjust arc harshness, and Arc Start to control the wire starting speed.

FAN ON DEMAND™

The Fan-on-Demand™ cooling system uses less power and generates less noise by only operating when needed, meaning improved efficiency, less maintenance and a safer working environment.

DIGITAL METERS

Digital Volt and Amp meters retain last weld information and allow precise set-up.

SPOOL CAPACITY

Suits 5kg & 15kg spool.



PRIMARY VOLTAGE	RATED PRIMARY CURRENT	MAX. PRIMARY CURRENT	REC. GEN. kVA*	RATED OUTPUT @ 40C (10 MIN)	WELDING CURRENT RANGE	SIZE OF WIRE/ ELECTRODE RANGE (MM)	SHIPPING INFO	IP RATING
380/415 Vac - 50/60Hz 3 Phase	28.7 Amps	37 Amps	25 kVA	Stick (MMA) - 490 A at 39.6 V, 60% Duty Cycle 387 A at 33.4 V, 100% Duty Cycle	37 - 500 Amps	Carbon Arc Max. 8mm	Machine Weight: 96kg	IP21S
				TIG - 500 A at 30 V, 60% Duty Cycle 387 A at 25.5 V, 100% Duty Cycle			Shipping Weight: 138kg	
				MIG - 500 A at 39 V 60% Duty Cycle 387 A at 33.4 V 100% Duty Cycle		0.9 - 1.6 solid 0.9 - 1.6 cored	L: 1100mm W: 570mm H: 1080mm	

*Due to variation between generators by different manufacturers, it is impossible for WIA to validate operation from all generators. Therefore, WIA recommends that operation of equipment on the generator is confirmed before purchasing either welder or the generator.

Arc & TIG Inverters

**RELIABLE, PORTABLE & COMPACT
FOR ONSITE & FIELD MAINTENANCE.**

- Generator compatible* – tolerant to unconditioned power from generators.
- Built in operator safety.
- Hot Start for manual arc – for even better arc starting.
- Arc Force – constantly monitors arc voltage and boosts output if low arc voltage occurs.
- Lift Arc TIG Start – eliminates scratch starting and tungsten electrode damage.

Weldarc 145i

Part No: MC106-0

 **DIGITAL DISPLAY**
 **STICK**
 **DC TIG**
 **LIFT ARC START**

WELDARC 145i KEY FEATURES

- 145 Amp Arc & TIG welder
- Compact, lightweight design
- Suits 2.5 - 3.2mm electrodes
- 10 A supply plug
- Fan-on-Demand™
- Padded shoulder strap

PACKAGE INCLUDES

- Heavy Duty Work Clamp (3m)
- Industrial Twist Lock Electrode Holder (4m)
- Padded Shoulder Strap

OPTIONAL VRD

When activated by a WIA service agent, VRD (Voltage Reduction Device) delivers added safety when operating in Stick mode and meets the requirements of site work. Fully compliant to Australian Standards AS60974.1 & AS1674.2 CAT C.

10 AMP PLUG

Comes with a 10 Amp plug to suit common power supply outlets, making onsite maintenance easy and convenient.

EASY SET-UP & ADJUSTMENT

The control panel allows single knob adjustment indicated on the digital display.

PORTABLE

At only 4.1kg, the Weldarc 145i can go wherever the job takes you, making it ideal for onsite maintenance.

FAN-ON-DEMAND™

Power source cooling fan operates only when needed - reducing noise, energy use and the amount of contaminants pulled through the machine.



PRIMARY VOLTAGE	RATED PRIMARY CURRENT	MAX. PRIMARY CURRENT	REC. GEN. kVA*	SUPPLY PLUG	RATED OUTPUT @ 40C (10 MIN)	WELDING CURRENT RANGE	ELECTRODE SIZE RANGE (MM)	SHIPPING INFO	MACHINE WEIGHT	IP RATING
240 Vac - 50/60 Hz	10 Amps	25 Amps	6 kVA	10 Amps	145 A at 25.8 V, 15% Duty Cycle 56 A at 22.2 V, 100% Duty Cycle	20 - 145 Amps	2.5 - 3.2	7.2kg H: 320mm W: 220mm L: 450mm	4.1kg	IP21S

*Due to variation between generators by different manufacturers, it is impossible for WIA to validate operation from all generators. Therefore, WIA recommends that operation of equipment on the generator is confirmed before purchasing either welder or the generator.

Weldarc 185i

Part No: MC107-0

 **DIGITAL DISPLAY**
 **STICK**
 **DC TIG**
 **LIFT ARC START**

WELDARC 185i KEY FEATURES

- 185 Amp Arc & TIG welder
- Compact, lightweight design
- Suits 2.5 - 4.0mm electrodes
- 15 A supply plug
- Fan-on-Demand™
- Includes padded shoulder strap and carry case

PACKAGE INCLUDES

- Heavy Duty Work Clamp (3m)
- Industrial Twist Lock Electrode Holder (4m)
- Padded Shoulder Strap
- Carry Case

VRD

A built in VRD (Voltage Reduction Device) delivers added safety when operating in Stick or Lift-TIG mode and meets the requirements of site work. Fully compliant to Australian Standards AS 60974.1 and AS1674.2 CAT C.

FAN-ON-DEMAND™

Power source cooling fan operates only when needed - reducing noise, energy use and the amount of contaminants pulled through the machine.

PORTABLE

At only 5.5kg, the Weldarc 185i can go wherever the job takes you, making it ideal for onsite maintenance.

EASY SET-UP & ADJUSTMENT

The control panel allows single knob adjustment indicated on the digital display.



PRIMARY VOLTAGE	RATED PRIMARY CURRENT	MAX. PRIMARY CURRENT	REC. GEN. kVA*	SUPPLY PLUG	RATED OUTPUT @ 40C (10 MIN)	WELDING CURRENT RANGE	ELECTRODE SIZE RANGE (MM)	SHIPPING INFO	MACHINE WEIGHT	IP RATING
240 Vac - 50/60 Hz	14.7 Amps	32 Amps	10 kVA	15 Amps	185 A at 27.4 V, 20% Duty Cycle 80 A at 23.2 V, 100% Duty Cycle	20 - 185 Amps	2.5 3.2 4.0	10.7kg H: 420mm W: 190mm L: 540mm	5.5kg	IP23S

*Due to variation between generators by different manufacturers, it is impossible for WIA to validate operation from all generators. Therefore, WIA recommends that operation of equipment on the generator is confirmed before purchasing either welder or the generator.





ARC & TIG

Weldarc 200i AC/DC

✓ ALUMINIUM TIG WELDING

✓ HF PULSE START

✓ STICK



KEY FEATURES

- 200 Amp AC or DC TIG
- AC TIG for Aluminium
- 170 Amp Stick welder
- TIG HF Pulse Arc Start or TIG Lift Arc Start
- Pulse TIG
- Suits 2.0 - 4.0mm electrodes
- 15 Amp supply plug

8M TIG TORCH WITH TRIGGER & CURRENT CONTROL

Part No: MC105-0

DC TIG

DC TIG can be used for all steel, stainless steel, copper, copper alloys and titanium. When welding in DC current HF Pulse start allows easy not contact starts for critical applications.

VRD

A built in VRD (Voltage Reduction Device) delivers added safety when operating in Stick or Lift-TIG mode and meets the requirements of site work. Fully compliant to Australian Standards AS 60974.1 and AS1674.2 CAT C.

AC TIG

AC can be used specifically for TIG welding aluminium and aluminium alloys. The balance between positive and negative can be adjusted to control the amount of oxide cleaning for a more penetrating weld. When welding in AC current HF pulse start allows easy arc starting when welding aluminium.

INTEGRATED GAS VALVE

HF PULSE START

HF Pulse is a non-contact arc starting method allowing easy arc start without the interference problems with conventional HF and eliminates tungsten contamination. Available in AC or DC TIG mode.

PORTABLE

At 19.5kg, the Weldarc 200i can go wherever the job takes you, making it suitable for onsite maintenance.

PACKAGE INCLUDES

- Work Lead (3m)
- Industrial Twist Lock Electrode Holder (3m)
- TIG Torch with in-built trigger and current control (8m)
- Gas Regulator

PULSE TIG

The Pulse TIG features allows the user to adjust current peak and pulse frequency. Pulse TIG reduces heat input to material but still allowing filler metal melt, and maintains good penetration. Useful on thin materials, and near edges.

PRIMARY VOLTAGE	RATED PRIMARY CURRENT	MAX. PRIMARY CURRENT	REC. GEN. kVA*	SUPPLY PLUG	RATED OUTPUT @ 40C (10 MIN)	WELDING CURRENT RANGE	ELECTRODE SIZE RANGE (MM)	SHIPPING INFO	MACHINE WEIGHT	IP RATING
240 Vac - 50/60 Hz	13 Amps	34 Amps	10 kVA	15 Amps	Stick MMA -170 A at 26.8 V, 15% Duty Cycle, 66 A at 22.6 V, 100% Duty Cycle	5 - 170 Amps	2.0 2.5 3.2	30.5kg L: 770mm W: 335mm H: 460mm	19.5kg	IP21S
					TIG - 200 A at 18 V, 15% Duty Cycle, 77 A at 13.1 V, 100% Duty Cycle	5 - 200 Amps	4.0			

*Due to variation between generators by different manufacturers, it is impossible for WIA to validate operation from all generators. Therefore, WIA recommends that operation of equipment on the generator is confirmed before purchasing either welder or the generator.



Distributed By:

Issued February 2020



Trusted by the best

welding.com.au
1300 300 884