

CYLINDERS

Tesuco has a range of disposable cylinders to compliment the different portable brazing equipment that is available. In many cases, disposable cylinders are more convenient and can realise savings when compared to refillable cylinders.

MAXY GAS

Maxy Gas is a fuel gas in a disposable cylinder. It is designed for use with the Turbo Set 90, which is aimed at the Jewellery and hobbyist markets. With oxygen, this gas has a flame temperature of 3,050°C, making it ideal for many applications.

| Specifications | |
|--|--|
| Packaging Type | Cardboard Box (Carton of 12) |
| Dimensions Carton of 12 Product Only | (H) 290 mm (W) 310 mm (D) 240 mm (H) 270 mm (Ø) 73.8 mm |
| Materials of Construction | Aluminium |
| Operating Temperature | Not to Exceed +50°C |
| DG Classification | 2.1 |
| Outlet Connection | 7/16" |
| Warranty | 1 Year (Manufacturer's Defect) |
| Country of Origin | Italy |



| Part No | Application | Volume | UN No. | Weights (kg) | |
|---------|-------------|--------|--------|--------------|----------------------|
| | | | | Nett | Gross (Carton of 12) |
| OTMB | OTS90 Set | 350 g | 2037 | 0.50 | 6.40 |

MAP-PRO™

MAP-Pro™ is a fuel gas in a disposable cylinder. It is designed for use with the Turbo Set 200, which is aimed at the plumbing, air conditioning, refrigeration and other professional trades markets. With oxygen, it has a flame temperature in excess of 3,000°C, making it ideal for many applications requiring a higher temperature than LPG on its own.

| Specifications | |
|--|--|
| Packaging Type | Cardboard Box (Carton of 12) |
| Dimensions Carton of 12 Product Only | (H) 280 mm (W) 455 mm (D) 155 mm (H) 270 mm (Ø) 75 mm |
| Materials of Construction | Steel |
| Operating Temperature | Not to Exceed +49°C |
| DG Classification | 2.1 |
| Outlet Connection | CGA 680 |
| Warranty | 1 Year (Manufacturer's Defect) |
| Country of Origin | USA |



| Part No | Application | Volume | UN No. | Weights (kg) | |
|---------|-------------|--------|--------|--------------|----------------------|
| | | | | Nett | Gross (Carton of 12) |
| OTMP | OTS200 Set | 400 g | 1077 | 0.81 | 10.24 |

OXYGEN CYLINDER

Oxygen is in a disposable cylinder. It is designed for use with the Turbo Set 90 and Turbo Set 200. With fuel gases such as Maxy Gas and MAP-Pro™ gas the flame temperature is in excess of 3,000°C, making it ideal for many applications requiring a higher temperature than LPG on its own.

| Specifications | |
|--|--|
| Packaging Type | Cardboard Box (Carton of 12) |
| Dimensions Carton of 12 Product Only | (H) 325 mm (W) 305 mm (D) 230 mm (H) 305 mm (Ø) 70.7 mm |
| Materials of Construction Cylinder Valve | Steel Brass |
| Operating Temperature | Not to Exceed +50°C |
| DG Classification | 2.2 Sub-Class 5.1 |
| Outlet Connection | M12 x 1 mm RH Male |
| Volume | 0.1 m ³ |
| Cylinder Pressure | 11,000 kPa |
| Test Pressure | 16,000 kPa |
| Water Capacity | 1 L |
| Warranty | 1 Year (Manufacturer's Defect) |
| Country of Origin | Italy |



| Part No | Application | Formula | UN No. | Weights (kg) | |
|---------|-------------------------|----------------|--------|--------------|-------------------------|
| | | | | Nett | Gross (Carton of 12) |
| OOB | OTS90 Set OTS200 Set | O ₂ | 1072 | 1.31 | 16.24 |