

DRAUGHT BEER PRODUCTS – REGULATORS



MEETS AS4267



Specifications	
Maximum Working Pressure	20,000 kPa
Delivery Pressure	0 – 400 kPa
Inlet Connection	Type 30 Stem and Nut
Outlet Connection	5/8-18 UNF RH with Nut and 5 mm Hose Barb

Part No	Description
RC1SCD04	Single Stage CO ₂ Regulator for Naturally Ventilated Areas. Built-In Relief Valve and Non-Return Valve Fitted to Outlet.
RCTWIN04A	Twin Single Stage CO ₂ Regulators for Naturally Ventilated Areas. Built-In Relief Valves and Non-Return Valves Fitted to Outlets. Each Regulator is Independently Adjustable with Its Own Pressure Gauge.



MEETS AS5034

Specifications	
Maximum Working Pressure	20,000 kPa
Delivery Pressure	0 – 400 kPa
Inlet Connection	CO ₂ : Type 30 Stem and Hand Wheel N ₂ : Type 50 Stem and Hand Wheel
Outlet Connection	5/8-18 UNF RH with Nut and 6 mm Hose Barb
Relief Valve	High Volume Set at 440 kPa

Part No	Description
RC1SCD4RW	Single Stage CO ₂ Regulator with High Flow Relief Valve, Non-Return Valve on Outlet, Gauge Protectors, Wire Attachment and Soft Seal Easyfit Hand Wheel. Supplied as Standard with 6 mm Hose Barbs, 10 mm hose barbs are available.
RC1SNI4RW	Single Stage N ₂ Regulator with High Flow Relief Valve, Non-Return Valve on Outlet, Gauge Protectors, Wire Attachment and Soft Seal Easyfit Hand Wheel. Supplied as Standard with 6 mm Hose Barbs, 10 mm hose barbs are available.
H3HB10	Hose Barb 3/8" Bullnose to 10 mm Barb



MEETS AS5034

Specifications	
Maximum Working Pressure	20,000 kPa
Delivery Pressure	0 – 400 kPa
Inlet Connection	CO ₂ : Type 30 Stem and Hand Wheel N ₂ : Type 50 Stem and Hand Wheel
Outlet Connection	1/2" BSP RH with Nut and 6 mm Hose Barb
Relief Valve	High Volume Set at 440 kPa

Part No	Description
RGC2SCD4HS	Two Stage CO ₂ Regulator with High Flow Relief Valve, Non-Return Valve on Outlet, Gauge Protectors and Soft Seal Easyfit Hand Wheel. Supplied as Standard with 6 mm and 10 mm Hose Barbs.
RGC2SNI4HS	Two Stage N ₂ Regulator with High Flow Relief Valve, Non-Return Valve on Outlet, Gauge Protectors and Soft Seal Easyfit Hand Wheel. Supplied as Standard with 6 mm and 10 mm Hose Barbs.