

## Pressure Regulators

### Model 825

In this Regulator you get extra strength, safety and large flows with excellent regulating characteristics. Combined with the latest in design, safety and quality.

**Features Include- Wt. 1.8kg**

- ▶ Rugged all metal construction
- ▶ Monel filter to improve life; easily changed
- ▶ Accurate - full cylinder pressure is controlled by the large 70mm diaphragm
- ▶ Large flows
- ▶ Safe, modern, proven seat design
- ▶ Large, easy to read colour coded gauges with safety seals
- ▶ Complies to AS 4267
- ▶ Built in burst relief
- ▶ Unique extra safety of the Snap Safe valve, built into inlet stem. Protects if a cylinder falls over. Applies to regs with an SS in description



825



825Z064



825ET8000X23

825EX150AC33	Acetylene 150K SS Vert. Inlet
825Z016	Oxygen 400 K SS Vert. Inlet
825EX10000X3	Oxygen 1000K SS Vert. Inlet
825X10000X33	Oxygen 1000K SS Side Inlet
825Z005	Propane 400 K SS Side Inlet
825Z064	Oxygen 1500K SS Vert. Inlet
825X15000X33	Oxygen 1500K SS Side Inlet
825Z084	Nitrogen 1000K SS Side Inlet
825Z085	Nitrogen 1500K SS Side Inlet
825EX1000ARG	Argon 1000K SS Vert. Inlet
825EA1000HE	Helium 1000K Vert. Inlet
825EA1000H30	Hydrogen 1000K Vert. Inlet
8251000CD206	CO2 1000K Side Inlet
825Z080	Nitrogen 4000K Vert Inlet
825Z066	HP SS diaphragm 1000K Vertical Inlet
825ET8000X23	Oxygen 800K Sav 'T' Lock V.I.
825ET800AR47	Argon 800K Sav 'T' Lock V.I.
825ET800N473	Nitrogen 800K Sav 'T' Lock V.I.
825TX400NII	*Nitrogen 400K Sav 'T' Lock V.I.
825DT400CDII	*CO2 400K Sav 'T' Lock
	*Internal self reseating safety relief valve