




1/55 Newton Road  
 Wetherill Park  
 NSW 2164  
 Tel: 02 96045022  
 Fax: 02 96045444

## *Inverter Spot Welder Model S13000 XLC*


- Single sided gun **L**, **X** gun and **C**- gun
- 8" LCD display
- Air pressure, Voltage testing, Offset Voltage, Temperature sensor monitoring, Lack of phase, Over-current, Thermal protections
- Fan cooling cable and water cooled C gun
- Single and double pulse welding
- Input voltage: 50/60Hz 380-415V/3ph
- No-load Voltage (V) 4-21V DC
- Maximum welding current (A) 12000 Amps
- Maximum current (A) 13000 Amps
- Maximum absorbed power (KW) 73KW
- Rated power X=50% (KW) 25KW
- Power factor 0.8
- Maximum welding thickness (mm) 4+4 or 2+2+2
- Maximum electrodes power 8bar (daN) X-Gun 345 ; C-Gun 350(600Lb)
- Duty cycle 5%
- Insulation class H
- Protection degree IP22
- Dimension (mm) 800x730x1260mm
- Net weight (kg) 170kg
- CE certificate registration number 7141000910 (S12-3)



Part No: CA600wc  
(Optional)



Part No: CA300wc  
(Standard)



Part No: CA110wc  
(Standard)



Part No: CAwheelarch  
(Standard)

