

1/55 Newton Road Wetherill Park NSW 2164

Tel: 02 96045022 Fax: 02 96045444

Inverter Spot Welder Model S14000 XLC

- Single sided gun L, X gun and C- gun
- 8" LCD display
- Memory automatic intelligent welding system, memory card and automatic detection of the thickness to be welded and variety welding parameters can be adjusted by intelligent system with record function, expert mode function, air pressure, voltage testing, offset voltage, temperature sensor monitoring, lack of phase, over-current, voltage protection, thermal protections, cooling fluid monitoring
- Water cooling cable, C gun, X gun, arm sets, radiator, transformer and diode
- Single and double pulse welding, no spark welding
- Input voltage: 50/60Hz 380-415V/3ph
- No-load Voltage (V) 4-21V DC
- Maximum welding current (A) 14000 Amps
- Maximum current (A) 15000 Amps
- Maximum absorbed power (KW) 85KW
- Rated power X=50% (KW) 30KW
- Power factor 0.8
- Maximum welding thickness (mm) 5+5 or 3+3+3
- Maximum electrodes power 8bar (daN) X-Gun 400; C-Gun 450(600Lb)
- Duty cycle 10%
- Insulation class H
- Protection degree IP22
- Dimension (mm) 800x730x1260mm
- Net weight (kg) 210kg
- CE certificate registration number 7141000910 (S12-3)



Part No: CA600wc (Optional)



Part No: CA300wc (Standard)



WVERTER SPOTTER

Part No: CA110wc (Standard)



Part No: CAwheelarch (Standard)





