

## **Pallet Truck**

## Model: TPT-3T

## Stronger, higher capacity, low maintenance unit for professional use

- Capacity: 3,000 kg (3.0T) higher rating than most others
- Fork dimensions: 1200mm x 685mm (outside width)
- Fork size: 160 x 60 mm
- Minimum height: 80mm
- Made from 4mm alloy steel plate making the strength 6 times higher than standard mild steel
- Reinforcing rib design under support frame for higher strength
- One piece Cast Steel pump design is leak proof, minimises maintenance & extends service periods
- Fitted with grease nipples for lubrication to bearings
- Polyurethane wheels for smooth & quiet operation (Tandem Loading Wheels 80 mm dia x 70 mm, Dual Rear Steering Wheels 180 mm dia x 50mm with strong cast iron hubs)
- 3 position hand control (Raise, Neutral, Lower) plus foot release lever for lowering
- Ergonomically comfortable 30mm hand grip size with rubber wrap for comfort, strength & ease of use
- Tight 180 deg turning circle

Capacity	Fork Dimensions	Fork Size	Minumum
KG	(Outside Width)	mm	Height mm
3000	1200 x 685	160 x 160	80





email: sales@garrickherbert.com.au Phone: 02 9545 6633 web: www.garrickherbert.com.au