

Upgrade to larger view, 4 sensors & ultra-clear vision!

2 year Warranty

Ultra Clear Vision

4 Arc Sensors
for reliable arc detection & switching

Generous Viewing Area
Larger than many other helmets in this class (100 x 53mm)

Reliable Power Source
Replaceable battery, solar assist, efficient electronics for low power consumption

Magnification Lens Holder

Light Weight & Comfortable

AS1337.1 High-Impact Rated
A must for many work sites

Grind-Mode
Locks the lens in light shade at the flick of a switch.



Now with Enhanced
COLOUR RECOGNITION

Shade, Sensitivity & Delay Adjustments

Precise & easy-to-use controls



- Ideal for MIG & Stick Welding, also suits TIG welding down to 30 amps
- Fast & easy cover lens replacement
- "Full Laminated" lens construction: Each layer in lens assembly is laminated for superior optical quality and reliability
- Bonus helmet bag

For more info





Part No.	Description	Unit	Inner Qty	Outer Qty
WC-05313	Blue	Each	1	4
WC-05314	Fire Metal	Each	1	4

Technical Data

Suitable Welding Processes	MIG, MMA/Stick & TIG (≥ 5 amps), Grinding
Suitable Applications	Light industrial & maintenance, Rural, etc
Switching Speed	Conforms to & exceeds requirements of AS/NZS 1338.1 Standard
Arc Sensing	4 Sensors
TIG Optimised	Yes. Suitable for low-amp TIG down to 30 amps
Power Supply	1 x CR2032 replaceable battery & Solar assist
On / Off	Ready to use at any time, no switching required
Inactive Shade (Grind/Off)	Shade 4
Active Shade (Weld)	9-13
Sensitivity	Low – High
Delay	0.1 – 1.0 seconds
Grind Mode	Switchable On/Off
Weight	480g
Viewing Area	100x53 mm
Cover Lens - Inner	116 x 95mm – Part No. WC-05321 (pkt 5)
Cover Lens – Outer	115 x 104mm – Part no. WC-05323 (pkt 10)
Magnification Lens Holder	Takes standard 108x51mm Magnification Lenses
Standards Compliance	Lens: AS/NZS1338.1, EN379, ANSI Z87.1, CSA Z94.3 Shell: AS/NZS1337.1 High Impact EN 175 B, ANSI Z87.1, CSA Z94.3
Optical Rating	1/1/1/2 (Optical quality / Diffusion of light / Variation in luminous transmittance / Angle dependency)
Warranty	2 years (on auto darkening lens)
Temperature Range	Operating -5 °C to +55 °C / Storage -10 to +65 °C

