



ADVANCED POWER™

Workmate™

PORTABLE GENERATORS

POWERED by **HONDA**™

LINZ
ELECTRIC
The Electric Generation

KOHLER

Reliable generators, built to last. Ideal for trades, rural, emergency back-up or anywhere else portable clean power is needed.



- Thoroughly tested and built by Australia's leading manufacturer of generating sets
- 3 Years Warranty backed by National Service Network #
- Low Oil Protection and Overload Circuit Breaker fitted to all models
- Trade tough fully welded frame with heavy duty anti-vibration mounts
- Brushless, totally maintenance-free alternators
- Overhead valve, 4 stroke, unleaded engines with cast iron cylinder sleeves
- All ELP models have alternator-mounted Residual Current Device (RCD) Protection
- All Workmate™ models available as Builder's Special fitted with Earth Leakage Protection (ELP), Weatherproof Outlets and Roll Over Frame to comply with WorkCover requirements *
- Diesel Option available on most sets



THD <5% as seen on a oscilloscope



* WorkCover requirements may vary between States & Territories and is subject to specific site conditions and requirements.

3 Year Warranty applies to all Honda™ and Kohler™ Workmate™ sets only.
2 Year Warranty applies to all Vanguard™ Workmate™ sets.

1300 733 004

m|power



Standard 240 Volt Single Phase Petrol Generators



Scoop Frame

Model	APH25RS1	APH33RS1
Watts Continuous	2000	2640
Amps Continuous	8.3	11.0
Alternator kVA	2.6	3.5
240V / 50 Hz	✓	✓
Engine Type	HONDA	HONDA
Engine Model	GX160	GX200
Start Type	Recoil	Recoil
Fuel Tank Capacity (Litres)	3.6	3.6
Approx. Running Time (Hours)	3.5	3
Approx. Noise Level dBA @ 7m	70	70
Weight	37	40
Length	620	620
Width	380	380
Height	380	380



Fuel Tank Base

Model	APB90ESS1V	APH105ES1	APH125ES1	APK150ES1
Watts Continuous	7200	8400	10000	12000
Amps Continuous	30.0	35.0	39.7	49.7
Alternator kVA	8.0	10.0	12.0	15.0
240V / 50 Hz	✓	✓	✓	✓
415V 3 Phase Option Available		✓		✓
Engine Type	VANGUARD	HONDA	HONDA	KOHLER
Engine Model	BS 303447	GX630	GX630	CH703S
Start Type	Electric	Electric	Electric	Electric
Fuel Tank Capacity (Litres)	25	35	35	35
Approx. Running Time (Hours)	8.5	9.0	8.5	6.5
Approx. Noise Level dBA @ 7m	74	74	75	76
Weight	109	130	139	148
Length	790	850	850	950
Width	520	580	580	625
Height	660	710	710	790



Roll Over Frame

Model	APH44RS1	APH58RS1	APH70RS1	APH70ES1	APH80RS1	APH80ES1	APB90RS1	APB90ES1
Watts Continuous	3520	4640	5600	5600	6400	6400	7200	7200
Amps Continuous	14.6	19.3	23.3	23.3	25.0	25.0	30.0	30.0
Alternator kVA	4.2	6.0	7.0	7.0	8.0	8.0	8.0	8.0
240V / 50 Hz	✓	✓	✓	✓	✓	✓	✓	✓
415V 3 Phase Option Available			✓	✓				
Engine Type	HONDA	HONDA	HONDA	HONDA	HONDA	HONDA	VANGUARD	VANGUARD
Engine Model	GX270	GX340	GX390	GX390ES	GX390	GX390ES	BS 295442	BS 295447
Start Type	Recoil	Recoil	Recoil	Electric	Recoil	Electric	Recoil	Electric
Fuel Tank Capacity (Litres)	6.5	6.5	6.5	6.5	6.5	6.5	8.5	8.5
Approx. Running Time (Hours)	3.0	2.8	2.6	2.6	2.6	2.6	2.8	2.8
Approx. Noise Level dBA @ 7m	71	71	74	74	74	74	74	74
Weight	60	71	77	82	82	82	84	84
Length	780	800	800	800	800	800	800	800
Width	500	500	500	500	500	500	500	500
Height	565	600	600	600	600	600	600	600



Workmate™ ELP

240 Volt Single Phase Petrol Generators with On-Board RCD

- Fitted with alternator-mounted Earth Leakage Protection / Residual Current Device (RCD)
- Trips generator when earth leakage is detected
- Clean stable power with less than 5% THD (Total Harmonic Distortion)



Model	APH25RS1ELP	APH33RS1ELP	APH44RS1ELP	APH58RS1ELP	APH70RS1ELP	APH70ES1ELP	APH80RS1ELP	APH80ES1ELP
Watts Continuous	2000	2640	3520	4640	5600	5600	6400	6400
Amps Continuous	8.3	11.0	14.6	19.3	23.3	23.3	25.0	25.0
Alternator kVA	2.6	3.5	4.2	6.0	7.0	7.0	8.0	8.0
240V / 50 Hz	✓	✓	✓	✓	✓	✓	✓	✓
415V 3 Phase Option Available					✓	✓		
Engine Type	HONDA	HONDA	HONDA	HONDA	HONDA	HONDA	HONDA	HONDA
Engine Model	GX160	GX200	GX270	GX340	GX390	GX390ES	GX390	GX390ES
Start Type	Recoil	Recoil	Recoil	Recoil	Recoil	Electric	Recoil	Electric
Fuel Tank Capacity (Litres)	3.6	3.6	6.5	6.5	6.5	6.5	6.5	6.5
Approx. Running Time (Hours)	3.5	3	3.0	2.8	2.6	2.6	2.6	2.6
Approx. Noise Level dBA @ 7m	70	70	71	71	74	74	74	74
Weight	37	40	60	71	77	82	82	82
Length	620	620	780	800	800	800	800	800
Width	380	380	500	500	500	500	500	500
Height	380	380	565	600	600	600	600	600

Workmate™ Builders Special

Petrol Powered Generators with RCD, Weatherproof Outlets, Standard with tough fully welded Roll Over Frame



- Fitted with Earth Leakage Protection, auto-switched outlets, all contained within IP66-rated housing
 - Compliant for WorkCover and commercial use*
 - Optional starting battery on electric start models.
- * *Workcover requirements may vary between states and territories and is subject to specific site conditions and requirements.*

Model	APH25RS1BS	APH33RS1BS	APH44RS1BS	APH58RS1BS	APH70RS1BS	APH70ES1BS	APH80RS1BS	APH80ES1BS	APB90RS1VBS	APB90ES1VBS
Watts Continuous	2000	2640	3520	4640	5600	5600	6400	6400	7200	7200
Amps Continuous	8.3	11.0	14.6	19.3	23.3	23.3	25.0	25.0	30.0	30.0
Alternator kVA	2.6	3.5	4.2	6.0	7.0	7.0	8.0	8.0	8.0	8.0
240V / 50 Hz	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
415V 3 Phase Option Available					✓	✓				
Engine Type	HONDA	HONDA	HONDA	HONDA	HONDA	HONDA	HONDA	HONDA	VANGUARD	VANGUARD
Engine Model	GX160	GX200	GX270	GX340	GX390	GX390ES	GX390	GX390ES	BS 295442	BD 295447
Start Type	Recoil	Recoil	Recoil	Recoil	Recoil	Electric	Recoil	Electric	Recoil	Electric
Fuel Tank Capacity (Litres)	3.6	3.6	6.5	6.5	6.5	6.5	6.5	6.5	8.5	8.5
Approx. Running Time (Hours)	3.5	3	3.0	2.8	2.6	2.6	2.6	2.6	2.8	2.8
Approx. Noise Level dBA @ 7m	70	70	71	71	74	74	74	74	74	74
Weight	37	40	60	71	77	82	82	82	84	84
Length	620	620	780	800	800	800	800	800	800	800
Width	380	380	500	500	500	500	500	500	500	500
Height	380	380	565	600	600	600	600	600	600	600



Diesel Workmate™

Diesel Air-Cooled 3000RPM Portable Generators



- Diesel reliability and economy in a portable Workmate™ package
- Optional recoil start on 2.5kVA – 6kVA models
- Class leading Linz brushless totally maintenance-free alternator
- Optional AVR (Automatic Voltage Regulator) models available
- Mine Specification versions available

Model	APL25RS1D	APL40ES1D	APL60ESS1	APL75ES1DTB	APL100ES1DTB
Watts Continuous	2000	3200	4800	6000	8000
Amps Continuous	8.2	13.3	19.7	25.4	32.8
Alternator kVA	2.6	4.2	6.0	8.0	10.0
240V / 50 Hz	✓	✓	✓	✓	✓
Remote Start Capability		✓	✓	✓	✓
Engine Type	KOHLER	KOHLER	KOHLER	KOHLER	KOHLER
Engine Model	15LD225	KD440	KD440	KD500	KD425-2
Start Type	Recoil	Electric	Electric	Electric	Electric
Fuel Tank Capacity (Litres)	3	4.3	5	35	35
Approx. Running Time (Hours)	3.0	3.5	3.5	17.0	14.0
Approx. Noise Level dBA @ 7m	80	80	82	82	85
Weight	68	68	100	120	140
Length	590	800	800	850	950
Width	435	500	500	580	625
Height	525	600	600	710	790

KOHLER®

Workmate™ Upgrade Options



Earth Stake



ELP models fitted with on-board RCD



RCD & Weatherproof Outlets



Battery for Electric start models



Trolley Kit - 2 or 4 wheels



LifeGuard™ Generator Board



Lifting Eye



Containment Tray



High Clearance 4 Wheel Trolley Kit



M+H Power Systems Pty Ltd
 ABN 96 051 792 833
 Head Office: 9 Mosrael Place Rowville VIC 3178
 P: 1300 733 004 E: info@mpower.com.au
 F: 1300 733 005 W: www.mpower.com.au
 Australia, New Zealand and Fiji

Distributed by:



www.mpower.com.au