

## BE 75-16 (600580190) Drill

(220-240 V / 50 - 60 Hz); Cardboard box

- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Rotating carbon brush bridge for maximum performance even in anti-clockwise rotation, e.g. when removing jammed screws
- Vario (V)-electronics for working with customised speeds for the materials used
- Metabo S-automatic torque limiting clutch: mechanical decoupling of the drive if the drill jams for safe working
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Suitable for powerful drilling of larger diameters and for stirring thick liquid-like materials

### [Link to Product](#)

#### Illustration



Product may differ from Image

#### Characteristics

Rated input power	750 W
Output power	470 W
Drill Ø steel	16 mm / 5/8 "
Drill-Ø soft wood	50 mm / 2 "
No-Load Speed	0 - 660 /min
Revolutions at rated load	350 /min
Gears	1
Maximum torque	75 Nm / 664 in-lbs
Collar diameter	43 mm / 1 11/16 "
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "
Drill spindle with hexagonal recess	6.35 mm / 1/4 "

Drill spindle thread	1/2 " - 20 UNF
Weight (without power cable)	2.6 kg / 5.7 lbs
Cable length	2.6 m / 9 ft
<b>Vibration</b>	
Drilling in metal	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
<b>Noise emission</b>	
Sound pressure level	81 dB(A)
Sound power level	92 dB(A)
Uncertainty of measurement K	3 dB(A)