

B 32/3 (600323000) Drill

(220-240 V / 50 - 60 Hz); Cardboard box

- Powerful three-speed drill with extra high torque
- Core drilling up to Ø 100 mm combined with the magnetic drill stand M 100 (accessory 6.27100)
- Robust mechanical gearbox with oil bath lubrication
- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Vario (V)-electronics for working with customised speeds for the materials used
- Safety clutch: mechanical decoupling of the drive for safe working if the drill jams
- For easy drilling of larger diameters and driving in of very long screws

Link to Product

Illustration



Product may differ from Image

Characteristics		
Rated input power	1800 W	
Output power	1200 W	
Drill Ø steel	32 mm / 1 1/4 "	
Drill-Ø soft wood	70 mm / 2 3/4 "	
No-Load Speed	0 - 170 / 0 - 320 / 0 - 470 /min	
Revolutions at rated load	110 / 190 / 280 /min	
Gears	3	
Maximum torque	190 / 120 / 90 Nm // 1682 / 1062 / 797 in-lbs	
Collar diameter	65 mm / 2 9/16 "	
Drill spindle with inside taper	MT 3	
Weight (without power cable)	7.8 kg / 17.2 lbs	
·····9···(··········)		

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 11/15

Cable length	5 m / 16 ft	
Vibration		
Drilling in metal	3.5 m/s²	
Uncertainty of measurement K	1.5 m/s²	
Noise emission		
Sound pressure level	90 dB(A)	
Sound power level	101 dB(A)	
Uncertainty of measurement K	3 dB(A)	

The information in this brochure has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 11/15