

## SSW 650 (602204000) Impact Screwdriver

(220-240 V / 50 - 60 Hz); Cardboard box

- Extremely powerful for demanding screwing applications
- Low kick-back operation with extremely high torque
- Vario (V)-Electronics for working with customised speeds for the materials used
- Robust die cast aluminium gear housing for optimum heat dissipation and durability

### [Link to Product](#)

#### Illustration



Product may differ from Image

#### Characteristics

|                              |                             |
|------------------------------|-----------------------------|
| No-Load Speed                | 0 - 2100 /min               |
| Rated input power            | 650 W                       |
| Output power                 | 360 W                       |
| Maximum impact rate          | 2800 /min                   |
| Maximum torque               | 600 Nm / 450 ft. lbs        |
| Bit retainer                 | Male square 1/2" (12.70 mm) |
| Weight (without power cable) | 3 kg / 6.6 lbs              |
| Cable length                 | 5 m / 16 ft                 |

#### Vibration

|                              |                      |
|------------------------------|----------------------|
| Impact screwdriving          | 12 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

#### Noise emission

|                      |          |
|----------------------|----------|
| Sound pressure level | 98 dB(A) |
|----------------------|----------|

---

|                              |           |
|------------------------------|-----------|
| Sound power level            | 109 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

---