

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



Dy-Mark PROTECH® PENETRATING OIL



Dy-Mark PROTECH® Penetrating Oil is a high speed penetrant and lubricant that quickly penetrates rusted and seized metal parts. It has a low viscosity that creeps into cracks, seams, threads and joints, loosening and freeing them instantly.

Incorporates patented 2-way actuator with locking tab. Uses a 360° valve for upright inverted applications.

DIRECTIONS FOR USE

Recommended Uses:

Taps, nuts & bolts, rusted bolts, padlocks, pins, screws, bushings, clips, hinges, locks, washers and other rusted surfaces.

Application:

De-activate and isolate equipment before use. Shake can well. Shake can occasionally during use. **360 degree valve** enables spraying in upright and inverted positions. Do not spray at 45 degree angle. Spray liberal coating directly on to corroded surfaces, saturating the problem area. Use extension tube for hard to reach areas. Repeat application if necessary.

When finished spraying, actuator can be set in lock position to prevent accidental actuation.

TECHNICAL DATA

| | |
|---------------------|---------------------|
| Size: | 400g Aerosol |
| Colour: | Light Golden Yellow |
| Consistency: | Liquid |
| Propellant: | Carbon Dioxide |

STORAGE

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

DISPOSAL

Dispose of contents/container according to regional regulations.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



FIRST AID / SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website www.dymark.com.au or from the following QR code:



Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use, to determine the suitability of the product for the particular use intended.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.